



DS4 Base

DETECTION AND MEASUREMENT AREA SENSOR



Basic version of detection and measurement area sensors designed for simple applications. Reliable performance and ease of use ensure detection and measurement in industrial applications.

- Detection height from 300 to 1500 mm
- 5, 10, 25 mm pitch
- Operating distance up to 13 m
- IO-Link configuration
- Digital and analogue output (0...10 V or 4...20 mA)
- Basic configuration by wire



CODE DESCRIPTION

DS4 - 05 - 300 - B 05 - JA		
series	DS4	Area sensors detection and measurement
pitch	05	5 mm
	10	10 mm
	25	25 mm
controlled height	0300	300 mm
	0450	450 mm
	0600	600 mm
	0750	750 mm
	0900	900 mm
	1050	1050 mm
	1200	1200 mm
	1350	1350 mm
	1500	1500 mm
model	B	Model
receiver plug (M12)	05	5 poles
output	JA	Analogue V/A, IO-Link, Digital

TECHNICAL SPECIFICATIONS

DS4-05-****-B05-JA

**GENERAL DATA**

Operating principle	Emitter + Receiver
Detection capability	10 mm

MONITORED AREA

Nominal sensing distance	0.2 ... 5 m
Controlled height	300 ... 1500 mm

EMISSION DATA

Emission	Infrared (850 nm)
----------	-------------------

INPUT/OUTPUT

Output type	PNP or NPN or Push-Pull, 0...10V, 4..20 mA IO-Link
-------------	--

IO-LINK

IO-Link version	IO-Link V1.1.3
Transmission rate	230400 bits/s COM 3
Minimum cycle time	2 ms
DeviceID DEC	2
Process Data input length	32 Bytes
Process data output l	8 Bits

HMI/UI

LED Indicators (TX)	Green (Power ON), Yellow (Emission range) Red (Test, failure), Blue (Emission range)
LED Indicators (RX)	Green (Power ON), Yellow (Status output, Connection Active) Red (Hardware Errors, module occupied)

ELECTRICAL DATA

Supply voltage	19.2 ... 28.8 Vdc
Maximum No-load absorption	360 mA(emitter and receiver)
Power consumption - Emitter	≤ 2 W
Power consumption - Receiver	≤ 5 W
Maximum DC output voltage drop	2.5 V @ IL=100 mA
Maximum DC load current	100 mA

MECHANICAL DATA

Dimensions	35 x 40 x (307.5 ... 1507.5) mm
Material	Aluminium / PBT
Housing material	Aluminium
Active part material	PMMA
Optic window material	PMMA
Connections	M12 5 poles + 200 mm length cable TPU (TX), M12 5 poles + 200 mm length cable TPU (RX) (DS4-**-****B05-JA)
Weight	1.40 Kg/m (single bar, without package)

ENVIRONMENTAL DATA

Operating Temperature	-30 ... 55 °C (without freeze)
Storage temperature max.	-30 ... 70 °C
Mechanical protection	IP65 IP67
Shocks and vibrations	10 mm / 3g, 5 ... 150 Hz frequency, (EN 60068-2-6 / Class 3M7 IEC TR 60721-4-3); 25g x 6 ms x 600 (EN 60068-2-27 / Class 3M7 IEC TR 60721-4-3)
Humidity	15 ... 95 % (without freeze)

AVAILABLE MODELS

DS4 Base

DETECTION/MEASUREMENT AREA SENSORS

Distance between beams	Nominal sensing distance	Output type	Sensitivity adjustment	Response time	Controlled height	Beams number	PNP or NPN or Push-Pull , 0...10V, 4..20mA IO-Link
5 mm	0.2 ... 5 m	PNP or NPN or Push-Pull , 0...10V, 4..20mA IO-Link	High/Low emission (input emitter)	2.80 ms	300 mm	60	DS4-05-0300-B05-JA (957650001)
				3.70 ms	450 mm	90	DS4-05-0450-B05-JA (957650002)
				4.60 ms	600 mm	120	DS4-05-0600-B05-JA (957650003)
				5.50 ms	750 mm	150	DS4-05-0750-B05-JA (957650004)
				6.40 ms	900 mm	180	DS4-05-0900-B05-JA (957650005)
				7.30 ms	1050 mm	210	DS4-05-1050-B05-JA (957650006)
				8.20 ms	1200 mm	240	DS4-05-1200-B05-JA (957650007)
				9.10 ms	1350 mm	270	DS4-05-1350-B05-JA (957650008)
				10.00 ms	1500 mm	300	DS4-05-1500-B05-JA (957650009)
10 mm	0.2 ... 7 m			1.90 ms	300 mm	30	DS4-10-0300-B05-JA (957650048)
				2.35 ms	450 mm	45	DS4-10-0450-B05-JA (957650049)
				2.80 ms	600 mm	60	DS4-10-0600-B05-JA (957650050)
				3.25 ms	750 mm	75	DS4-10-0750-B05-JA (957650051)
				3.70 ms	900 mm	90	DS4-10-0900-B05-JA (957650052)
				4.15 ms	1050 mm	105	DS4-10-1050-B05-JA (957650053)
				4.60 ms	1200 mm	120	DS4-10-1200-B05-JA (957650054)
				5.05 ms	1350 mm	135	DS4-10-1350-B05-JA (957650055)
				5.50 ms	1500 mm	150	DS4-10-1500-B05-JA (957650056)
25 mm	0.2 ... 13 m			1.36 ms	300 mm	12	DS4-25-0300-B05-JA (957650095)
				1.54 ms	450 mm	18	DS4-25-0450-B05-JA (957650096)
				1.72 ms	600 mm	24	DS4-25-0600-B05-JA (957650097)
				1.90 ms	750 mm	30	DS4-25-0750-B05-JA (957650098)
				2.08 ms	900 mm	36	DS4-25-0900-B05-JA (957650099)
				2.26 ms	1050 mm	42	DS4-25-1050-B05-JA (957650100)
				2.44 ms	1200 mm	48	DS4-25-1200-B05-JA (957650101)
				2.62 ms	1350 mm	54	DS4-25-1350-B05-JA (957650102)
				2.80 ms	1500 mm	60	DS4-25-1500-B05-JA (957650103)

DS4 Base

MINIMUM DETECTABLE OBJECT

DETECTION/MEASUREMENT AREA SENSORS

	Minimum detectable object	Distance Lo	Distance Hi
DS4-05-****-B05-JA	10 mm	2.5 m	5 m
DS4-10-****-B05-JA	14 mm	4 m	7 m
DS4-25-****-B05-JA	30 mm	7 m	13 m

CONNECTIONS

DS4-**-****B05-JA
(Emitter (TX))


MALE
M12
5 pins

1	Brown	+24 Vdc
2	White	RANGE SELECT
3	Blue	0 Vdc
4	Black	NC
5	Grey	NC


DS4-**-****B05-JA
(Receiver (RX))

MALE
M12
5 pins

1	Brown	+24 Vdc
2	White	Analogue Output (A/V)
3	Blue	0 Vdc
4	Black	Digital / IO-Link
5	Grey	NO/NC, V/A Selection




DS4-10-****-B05-JA



(mm)

Models	A	L (mm)
DS4-10-0300-B05-JA	Pitch 10	309
DS4-10-0450-B05-JA		459
DS4-10-0600-B05-JA		609
DS4-10-0750-B05-JA		759
DS4-10-0900-B05-JA		909
DS4-10-1050-B05-JA		1059
DS4-10-1200-B05-JA		1209
DS4-10-1350-B05-JA		1359
DS4-10-1500-B05-JA		1509

MECHANICAL DRAWINGS



DS4 Base ACCESSORIES TO BE ORDERED SEPARATELY

DETECTION/MEASUREMENT AREA SENSORS

	Model	Description	Article code
Cables	CS-A1-03-U-03	Cable M12 5 poles axial female unshielded 3 m UL 2464	95ASE1170
	CS-A1-03-U-05	Cable M12 5 poles axial female unshielded 5 m UL 2464	95ASE1180
	CS-H2-03-B-01	Cascade cable for SH4 1 m	95ASE0031
	CS-H2-03-B-03	Cascade cable for SH4 3 m	95ASE0032
	CS-H2-03-B-10	Cascade cable for SH4 10 m	95ASE0033
	CD12M/0H-050A3	Connect.M12-F,5 poles-5m,PVC,Axial	CD12M/0H-050A3
	CD12M/0H-100A3	Connect.M12-F,5 poles-10m,PVC,Axial	CD12M/0H-100A3
	CDP12/0B-010AA	M12-F-Axial, 4p,M12-M-Axial,PVC,1 m	CDP12/0B-010AA
	CDP12/0B-030AA	M12-F-Axial, 4p,M12-M-Axial,PVC,3 m	CDP12/0B-030AA
	CDP12/0B-050AA	M12-F-Axial, 4p,M12-M-Axial,PVC,5 m	CDP12/0B-050AA
	CDP12/0B-100AA	M12-F-Axial, 4p,M12-M-Axial,PVC,10 m	CDP12/0B-100AA
	CV12/0B-00A	Connect.M12-M-Axial,4 p,Field attach.	CV12/0B-00A
	CV12/0B-00B	Connect.M12-M-90°,4 p,Field attach.	CV12/0B-00B
	CV12/0H-00A	Connect.M12-M-Axial,5 p,Field attach.	CV12/0H-00A
	CS-A1-03-U-10	Cable M12 5 poles axial female unshielded 10 m UL 2464	95ASE1190
	CS-A1-03-U-15	Cable M12 5 poles axial female unshielded 15 m UL 2464	95ASE1200
	CS-I1-02-B-03	CS-I1-02-B-03 4p M12-M/M12-F axial 3m bk	95ACC0009
	CS-M1-02-B-03	CS-M1-02-B-03 5p M12-F Lcode axial 3m gr	95ACC0007
	CS-A1-02-G-05	CS-A1-02-G-05 = M12 4-p axial 5m	95A251270
	CS-A1-02-G-03	CS-A1-02-G-03 = M12 4-p axial 3m	95A251380
	CS-A1-02-G-10	CS-A1-02-G-10 = M12 4-p axial 10m	95A251390
	CS-A1-02-R-02	CS-A1-02-R-02 = M12 4-p axial 2m PUR	95A251540
	CS-A1-02-R-05	CS-A1-02-R-05 = M12 4-p axial 5m PUR	95A251560
	CS-A1-02-U-03	Cable M12 4 poles axial female unshielded 3 m UL 2464	95ASE1120
	CS-A1-02-U-05	Cable M12 4 poles axial female unshielded 5 m UL 2464	95ASE1130
	CS-A1-02-U-10	Cable M12 4 poles axial female unshielded 10 m UL 2464	95ASE1140
	CS-A1-02-U-15	Cable M12 4 poles axial female unshielded 15 m UL 2464	95ASE1150
	CS-A1-02-B-NC	CS-A1-02-B-NC = M12 4-p axial PG	G5085002
Mounting brackets	ST-KSTD	Metal angled brackets 4 pcs kit for SG/SH4	95ACC1670
	ST-K40R	Orientable supports 4 pcs kit to be used with ST-KSTD	95ACC1680
	ST-K4AV	Anti vibration supports 4 pcs kit to be used with ST-KSTD	95ACC1700
	ST-K6AV	Anti vibration supports 6 pcs kit to be used with ST-KSTD	95ACC1710
	ST-KP4MP	Plastic angled brackets 4 pcs kit	95ASE1100
	ST-K4R0T-SH	Rotating brackets for SH4 4 pcs	95ASE0042
IO-Link masters	CBX-8IOL-PNIO	8P IOL M12 PROFINET MASTER	95ACC8190
	CBX-8IOL-EIP	8P IOL M12 EIP MASTER	95ACC8180

The company endeavors to continuously improve and renew its products; for this reason the technical data and contents of this catalogue may undergo variations without prior notice. For correct installation and use, the company can guarantee only the data indicated in the instruction manual supplied with the products. Product and Company names and logos referenced may be either trademarks or registered trademarks of their respective companies. We reserve the right to make modifications and improvements. These products are NOT safety sensors and are NOT suitable for use in personnel safety application.

Revision number: 3 - Revision date: 2025-06-04