



SG4 Extended

TYPE 4 SAFETY LIGHT CURTAIN WITH ADVANCED FUNCTIONALITY



Type 4 Finger and hand resolution safety light curtain with possibility of configuration of advanced functions through pushbuttons or Graphic User Interface.

- No dead zone
- Pigtail cable with M12 connector
- Cascade connection of up to 3 units
- Up to 20 m operating range and 1800 m protected height

- Compact dimensions (35 x 41 mm section)
- Anti-interference coding
- Integrated Muting function
- Floating Blanking, Fixed Blanking and Reduced Resolution
- Configurable with: Pushbuttons for common configuration
- Graphic User Interface for complete parametrization
- Ethernet Interface for programming, monitoring and error logging



CODE DESCRIPTION

SG 4 - 14 - 030 - 00 - P

serie	SG	SG4 Extended
type	4	Type 4
resolution	14	Finger: 14 mm
	30	Hand: 30 mm
monitored height	030	300 mm
	045	450 mm
	...	
	180	1800 mm
output	00	
functionality	P	Advanced (Muting, Blanking, Programmable with GUI)

TECHNICAL SPECIFICATIONS

	SG4-14-***-00-P	SG4-30-***-00-P
	SAFETY TYPE 4 	SAFETY TYPE 4 
GENERAL DATA		
Operating principle	Emitter + Receiver	
Detection capability	14 mm	30 mm
MONITORED AREA		
Nominal sensing distance	0.2 ... 7 m	0.2 ... 20 m
Controlled height	300 ... 1800 mm	
EMISSION DATA		
Emission	Infrared LED (950nm)	
Effective beam angle	≤ ±2.5 °	
FUNCTIONS		
Available functions	Manual/Automatic Restart, EDM, L/T Muting, Partial Muting, Override, Blanking, Programmability	
Included accessories	Standard “L” Mounting Brackets: 4 pcs kit, Standard “L” Mounting Brackets: 6 pcs kit	
SAFETY PARAMETERS		
Type	4	
PL	e	
SIL	SIL 3 (IEC 61508)	
INPUT/OUTPUT		
Output type	2 x PNP (OSSD safety output) with EDM	
COMMUNICATION		
Network Interface	10/100 Mbit/s Ethernet	
ELECTRICAL DATA		
Supply voltage	24 Vdc ±20%	
Power consumption - Emitter	≤ 3 W	
Power consumption - Receiver	≤ 5 W without load	
Maximum DC load current	500 mA each output	
MECHANICAL DATA		
Dimensions	306.3 (3540.75) mm	
Material	Painted aluminum / PMMA / PBT Valox 508 / PC LEXAN	
Connections	M12-5 poles pig-tail (emitter) M12-12 poles + M12-5poles / M12-12 poles pig-tails (receiver)	
Length of cables (Power)	≤ 50 m	
CERTIFICATIONS		
Shocks	16 ms (10 G) 1,000 shocks per axis (EN 60068-2-29)	
Vibrations	Width 0.35 mm, frequency 10 ... 55Hz; 20 sweep per axis, 1octave/min (EN 60068-2-6)	
Electromagnetic compatibility	IEC EN 60947-5-2	
ENVIRONMENTAL DATA		
Operating Temperature	0 ... 50 °C	
Storage temperature max.	-25 ... 70 °C	
Mechanical Protection	IP65	
Humidity	15 ... 95 % no condensation	
Ambient light immunity	According to IEC 61496-2	

AVAILABLE MODELS


Type	Detection capability	Nominal sensing distance	Controlled height	Beams number	Response time	Model
4	Finger prot. res. 14 programmable 14 mm	0.2 ... 7 m	300 mm	32	15 ms	SG4-14-030-00-P (957901240)
			450 mm	48	17 ms	SG4-14-045-00-P (957901250)
			600 mm	64	19 ms	SG4-14-060-00-P (957901260)
			750 mm	80	20 ms	SG4-14-075-00-P (957901270)
			900 mm	96	22 ms	SG4-14-090-00-P (957901280)
			1050 mm	112	24 ms	SG4-14-105-00-P (957901290)
			1200 mm	128	26 ms	SG4-14-120-00-P (957901300)
			1350 mm	144	27 ms	SG4-14-135-00-P (957901310)
			1500 mm	160	29 ms	SG4-14-150-00-P (957901320)
			1650 mm	176	31 ms	SG4-14-165-00-P (957901330)
			1800 mm	192	33 ms	SG4-14-180-00-P (957901340)
	Hand prot. res. 30 programmable 30 mm	0.2 ... 20 m	300 mm	16	13 ms	SG4-30-030-00-P (957901350)
			450 mm	24	14 ms	SG4-30-045-00-P (957901360)
			600 mm	32	15 ms	SG4-30-060-00-P (957901370)
			750 mm	40	16 ms	SG4-30-075-00-P (957901380)
			900 mm	48	17 ms	SG4-30-090-00-P (957901390)
			1050 mm	56	18 ms	SG4-30-105-00-P (957901400)
			1200 mm	64	19 ms	SG4-30-120-00-P (957901410)
			1350 mm	72		SG4-30-135-00-P (957901420)
			1500 mm	80	20 ms	SG4-30-150-00-P (957901430)
			1650 mm	88	21 ms	SG4-30-165-00-P (957901440)
			1800 mm	96		SG4-30-180-00-P (957901450)

SG4 Extended E_SERIE_PLUGS

SAFETY LIGHT CURTAINS

SG4-**-***-00-P (Receiver)


1	Brown	24 Vdc
2	Blue	0 Vdc
3	White	RESET/RESTART/ALIGN
4	Green	OVERRIDE1
5	Pink	OSSD2
6	Yellow	EDM
7	Black	MUTING DISABLE
8	Gray	OSSD1
9	Red	OVERRIDE2
10	Violet	LAMP OUTPUT
11	Gray/Pink	OVERRIDE STATUS
12	Red/Blue	EARTH



MALE
M12
12 pins Safety

SG4-**-***-00-P (Receiver)


1	Brown	24 Vdc
2	White	MUTING2
3	Blue	0 V
4	Black	MUTING1
5	Gray	NOT USED



MALE
M12
5 pins Safety

SG4-**-***-00-P (Emitter)


1	Brown	24 Vdc
2	White	TEST
3	Blue	0 V
4	Black	EARTH
5	Gray	RANGE REDUCTION



MALE
M12
5 pins Safety


SG4-**-***-00-P (Receiver)

1	Brown	24 Vdc
2	Blue	0 Vdc
3	White	RESET/RESTART/ALIGN
4	Green	TEACH IN
5	Pink	OSSD2
6	Yellow	EDM
7	Black	NOT USED
8	Gray	OSSD1
9	Red	TOLERANCE
10	Violet	LAMP OUTPUT
11	Gray/Pink	NOT USED
12	Red/Blue	EARTH



MALE
M12
12 pins Safety

MECHANICAL DRAWINGS



ACCESSORIES TO BE ORDERED SEPARATELY

	Model	Description	Article code
Laser pointers	SG-LP	Laser pointer for SG light curtains	95ASE5590
Mirrors	SG-DM-150	Deviating mirror for light curtains h=150mm	95ASE1670
	SG-DM-600	Deviating mirror for light curtains h=600mm	95ASE1680
	SG-DM-900	Deviating mirror for light curtains h=900mm	95ASE1690
	SG-DM-1200	Deviating mirror for light curtains h=1200mm	95ASE1700
	SG-DM-1650	Deviating mirror for light curtains h=1650mm	95ASE1710
	SG-DM-1900	Deviating mirror for light curtains h=1900mm	95ASE1720
Mirrors brackets	ST-PS-DM	SG-PSB protective stand mounting kit for mirror SG-DM 2 nuts	95ASE1770
	ST-DM	Deviating mirrors SG-DM mounting kit on SE-S columns	95ASE1940

SG4 Extended ACCESSORIES TO BE ORDERED SEPARATELY

SG4 Extended

SAFETY LIGHT CURTAINS

	Model	Description	Article code
Cables	CAB-ETH-M01	M12-RJ45 IP67 ethernet cable 1m	93A051346
	CS-G1-70-B-002	Pigtail cable for SG4 EXTENDED receiver blanking function M12 12p male connector 0.2m	95A252830
	CS-A1-03-U-03	Cable M12 5 poles axial female unshielded 3m UL 2464	95ASE1170
	CS-A1-03-U-50	Cable M12 5 poles axial female unshielded 50m UL 2464	95A252700
	CS-A1-03-U-05	Cable M12 5 poles axial female unshielded 5m UL 2464	95ASE1180
	CS-A1-03-U-10	Cable M12 5 poles axial female unshielded 10m UL 2464	95ASE1190
	CS-A1-03-U-15	Cable M12 5 poles axial female unshielded 15m UL 2464	95ASE1200
	CS-A1-03-U-25	Cable M12 5 poles axial female unshielded 25m UL 2464	95ASE1210
	CS-A1-10-U-03	Cable M12 12 poles axial female unshielded 3m UL 2464	95A252720
	CS-A1-10-U-05	Cable M12 12 poles axial female unshielded 5m UL 2464	95A252730
	CS-A1-10-U-10	Cable M12 12 poles axial female unshielded 10m UL 2464	95A252740
	CS-A1-10-U-25	Cable M12 12 poles axial female unshielded 25m UL 2464	95A252760
	CS-A1-10-U-15	Cable M12 12 poles axial female unshielded 15m UL 2464	95A252750
	CS-A1-10-U-50	Cable M12 12 poles axial female unshielded 50m UL 2464	95A252770
	CS-F1-80-B-01	Cascade cable for SG4 EXTENDED 1m	95A252840
	CS-F1-80-B-005	Cascade cable for SG4 EXTENDED 0.5m	95A252850
	CS-F1-80-B-0005	Cascade cable for SG4 EXTENDED 0.05m	95A252860
	CAB-ETH-M03	M12-RJ45 IP67 ethernet cable 3m	93A051347
	CAB-ETH-M05	M12-RJ45 IP67 ethernet cable 5m	93A051348
Mounting brackets	ST-K6AV	Anti vibration supports 6 pcs kit to be used with ST-KSTD	95ACC1710
	ST-KP4MP	Plastic angled brackets 4 pcs kit	95ASE1100
	ST-KP6MP	Plastic angled brackets 6 pcs kit	95ASE1110
	ST-K40R	Orientable supports 4 pcs kit to be used with ST-KSTD	95ACC1680
	ST-K60R	Orientable supports 6 pcs kit to be used with ST-KSTD	95ACC1690
	ST-KSTD	Metal angled brackets 4 pcs kit for SG/SH4	95ACC1670
	ST-K4AV	Anti vibration supports 4 pcs kit to be used with ST-KSTD	95ACC1700
Muting lamps	LMS-1	Modular muting lamp	95ACC1990
	LMS-2	Muting lamp horizontal fixing	95ACC2000
	LMS-3	Muting lamp vertical fixing	95ACC2010
	LMS	Muting lamp	95ASE1830
Protective stands	SG-PSB-600	Protective stand for light curtains h=600mm	95ASE2240
	SG-PSB-1000	Protective stand for light curtains h=1000mm	95ASE2250
	SG-PSB-1200	Protective stand for light curtains h=1200mm	95ASE2260
	SG-PSB-1650	Protective stand for light curtains h=1650mm	95ASE2270
	SG-PSB-1900	Protective stand for light curtains h=1900mm	95ASE2280
	SG-P	Plate with springs for protective stands SG-PSB and SG-PSM	95ASE2290
Protective stands brackets kit	ST-PS4-SG-SE	SG-PSB protective stand mounting kit for SG/SH4 4 brackets	95ASE1750
	ST-PS6-SG-SE	SG-PSB protective stand mounting kit for SG/SH4 6 brackets	95ASE1760
Safety control units	SG-BWS-T4-MT	Safety control unit for S5 SL5 S300 safety sensors pl=e double muting 4 beams	957051010
Safety units	SE-SR2	Safety unit 3NO + 1NC outputs	95ACC6170
	CSME-03VU24-Y14	Forced guided relay interface 3NO + 1 NC	95ASE1270
Vertical supports	SE-S-800	Column for light curtains and floor stand h=800 mm	95ACC1730
	SE-S-1000	Column for light curtains and floor stand h=1000 mm	95ACC1740
	SE-S-1200	Column for light curtains and floor stand h=1200 mm	95ACC1750
	SE-S-1500	Column for light curtains and floor stand h=1500 mm	95ACC1760
	SE-S-1800	Column for light curtains and floor stand h=1800 mm	95ACC1770

NOTE : When using CS-ME, connect EDM input, and be sure EDM function is active on the safety light curtain.

The company endeavors to continuously improve and renew its products; for this reason the technical data and contents of this catalogue may undergo variations without prior notice. For correct installation and use, the company can guarantee only the data indicated in the instruction manual supplied with the products. Product and Company names and logos referenced may be either trademarks or registered trademarks of their respective companies. We reserve the right to make modifications and improvements.