



LP4ER series

Light Curtains


Type 4



Light Curtains
Type 4

features

- Type 4 according IEC 61496-1 and IEC 61496-2
- Robust housing (50x60 mm) for applications in presence of heavy shocks and vibrations
- 40 mm resolution for hand protection and 2,3,4 beams for body protection/access control
- Operating distance up to 16 m (standard version) and up to 60 m (LONG RANGE version)
- Integrated functions: MANUAL/AUTOMATIC Restart, EDM and operating distance selectable
- Standard M12 5 poles connector on TX unit and M12 8 poles or M23 9 poles on RX unit



web contents



- Application notes
- Photos
- Catalogue / Manuals



code description

		LP4ER / 40 - 060 12
series	LP4	Type 4 safety light curtains 50 x 60 mm compact housing
couple	ER	Emitter + Receiver couple
beams	40	40 mm resolution; hand protection
	0A	2 beams resolution; body protection; 500 mm controlled height
	0B	3 beams resolution; body protection; 800 mm controlled height
	0C	4 beams resolution; body protection; 900 mm controlled height
height	050...120	Protected height from 500 to 1,200 mm
range		Standard model with selectable MANUAL/AUTOMATIC Restart and EDM functions
	L	Long range model
	12	Model with M12 connector on receiver unit

available models

2, 3, 4 beams resolution; 0...6 / 1...16 m controlled distance;
7 msec response time

protected height (mm)	n° of beams	model
510	2	LP4ER/0A-050
810	3	LP4ER/0B-080
910	4	LP4ER/0C-090

available models

40 mm resolution; 8...30 / 18...60 m controlled distance

protected height (mm)	n° of beams	response time (msec)	model
610	20	17	LP4ER/40-050L
910	30	23	LP4ER/40-090L
1,210	40	28.5	LP4ER/40-120L

available models

2, 3, 4 beams resolution; 8...30 / 18...60 m controlled distance

protected height (mm)	n° of beams	response time (msec)	model
510	2	500	LP4ER/0A-050L
			LP4ER/0A-050L12
810	3	800	LP4ER/0B-080L
			LP4ER/0B-080L12
910	4	900	LP4ER/0C-090L
			LP4ER/0C-090L12

technical specifications

LP4ER/**-***--		
	  	
operating voltage	19.2...28.8 Vdc	PELV power supplier according to EN 60204-1 Cap.6.4
power consumption, Receiver	6 W	no load
power consumption, Emitter	3 W	
output type	2 x PNP	OSSD safety outputs
output current	500 mA	higher values are considered overload
equivalent resistive load	48 Ω	lower values are considered short circuit
capacitive load	2 µF	lower values may be considered short circuit
recovery time	15 s	
response time OSSDs	30 ms	
OSSDs self test pulse duration	100 µs	
restart signal duration	100 ms	
Test signal duration	40 ms	
effective aperture angle (EAA)	≤ ± 2,5°	IEC 61496-1
artificial light rejection	according to IEC 61496-2	] according to the reported standards
ambient light rejection	according to IEC 61496-2	
IP mechanical protection	IP65	
operating temperature	0...+55°C	
storage temperature	-25...+70°C	to be respected also during transportation
humidity	95%	no condensation
vibrations	according to IEC 61496-1	] according to the reported standards
shocks	according to IEC 61496-1	
dimension	50 mm (front) x 60 mm	
S0 connectors Emitter	1 x M12 5p male	
S0 connectors Receiver	1x M23, 19p, male 1x M12, 8p, male (L12 male)	

electrical diagrams of the connections

LP4ER series					
pin	color	signal	type	description	
1	WH	N.C.	-	not connected	
2	RD	OSSD2	OUT	second safety static output (PNP)	
3	GY	OSSD1	OUT	first safety static output (PNP)	
4	YE	System Status + Sign. level	OUT	repetition of OSSDs status, see note + low signal level indication, see note	
5	GN	N.C.	- a b	not connected	
6	BU	0V _{cc}	POWER	supply voltage reference	
7	VT	N.C.	-	not connected	
8	GY - PK	N.C.	-	not connected	
9	RD - BU	N.C.	-	not connected	
10	WH - GN	N.C.	-	not connected	
11	BK	Abilitaz. EDM	IN	enabling for external contactor control	
12	WH - GN	PE	GND	earth protection connection	
13	WH - YE	Man. / Autom.	IN	selection of the Start/Restart mode	
14	BN - YE	start	IN	connection to the Start/Restart button	
15	WH - GY	N.C.	-	not connected	
16	BN - GY	N.C.	-	not connected	
17	WH - PK	N.C.	-	not connected	
18	BN - GN	EDM	IN	connection to the external control contacts	
19	BN	24V _{cc}	POWER	supply voltage input	


BK	black	OG	orange	YE	yellow	GY	grey
BN	brown	GN	green	WH	white	VT	violet
RD	red	BU	blue	PK	pink		

serie LP4ER					
pin	color	signal	type	description	
1	WH	OSSD1	OUT	first safety static output (PNP)	
2	BN	24V _{cc}	POWER	supply voltage	
3	GN	OSSD2	OUT	second safety static output (PNP)	
4	YE	EDM	IN	connection to the external control contacts (EDM) or connected at 0V to exclude EDM	
5	GY	Mode_A	IN	selection of the manual or automatic Start/Restart mode	
6	PK	Mode_B	IN	selection of the manual or automatic Start/Restart mode	
7	BU	0V	POWER	supply voltage reference	
8	RD	FE	GND	protection earth	


NOTE: On these models it is possible to choose the operating modes by changing the wiring. By using the EDM function it is possible to extend the safety control to the contactors controlled downstream, that must be the type with guided contacts and approved for safety applications.

dimensions (mm)

LP4ER/40-***L, LP4ER/0*-*** - Receiver




LP4ER/40-***L12, LP4ER/0*-***L, LP4ER/0*-***L12 - Emitter




dimensions	LP4ER/**-***			LP4ER/**-***L					
	0A-050	0B-080	0C-090	40-060	40-090	40-120	0A-050	0B-080	0C-090
A (TX)	736	1,036	1,136	736	1,036	1,336	736	1,036	1,136
B (protected height)	510*	810*	910*	610	910	1,210	510*	810*	910*
C (first beam quote)	120			76					

accessories

ST203 / outfit mounting accessories

product	to be used with	dimensions (mm)	description / installation
	LP4 series	 Technical drawing showing the dimensions of the fastening insert. The main view is a top view of a rectangular plate with two M6 holes. Dimensions: total width 60mm, total height 50mm, distance between hole centers 30mm, distance from top edge to first hole 10.5mm, distance from bottom edge to first hole 10.5mm, hole diameter 7.5mm, hole spacing from side edges 10.5mm. A side view shows a thickness of 3mm and a 3.75mm offset.	Fastening insert for 50x60 profile. Part of the standard kit Two pieces are provided for each bracket ST202.

ST202 / outfit mounting accessories

product	to be used with	dimensions (mm)	description / installation
	LP4 series	 Technical drawing showing the dimensions of the L Bracket. The main view is a top view of an L-shaped bracket. Dimensions: total width 105mm, total height 50mm, distance between hole centers 30mm, distance from top edge to first hole 13.5mm, distance from bottom edge to first hole 13.5mm, hole diameter 7.5mm, hole spacing from side edges 10.5mm. A side view shows a thickness of 3mm and a 3.75mm offset.	L Bracket Long bracket. Part of the standard kit. Two pieces are provided for each couples. Must be applied in the housin part of the body.