


**FEATURES:**

- Constant Current LED Driver
- High Efficiency: Up to 89%
- Active Power Factor Correction
- Short Circuit / Open Circuit Protection
- Meet UL, CE Safety Requirement
- Long Life, High reliability
- IP65/IP67 design for indoor/outdoor
- 5 Years Limited Warranty

**Models**  
**Single output**


Model	Max Output Power (W)	Output Voltage Range (V)	Output Current (mA)	Input Voltage (VAC/Hz)	Efficiency (%)
AMER40-4275Z	31.5	30-42	750	90-305/47-63	89
AMER40-4290Z*	37.8	30-42	900	90-305/47-63	89

NOTE: All specifications in this datasheet are measured at an ambient temperature of 25°C, humidity <75%, nominal input voltage and at rated output load unless otherwise specified.

**Input Specifications**

Parameters	Conditions	Typical	Maximum	Units
Input Current	90 VAC, full load		0.58	Arms
Inrush current <2ms	115 VAC, cold start		40	A
	277 VAC, cold start		60	
Leakage current			0.75	mA
Input dissipation	No Load		1.0	W
	Output Short		4.5	W
Power Factor	115 VAC, full load		0.98	
	277 VAC, full load		0.92	
Input Fuse		2 A / 300 VAC		
Start-up Time	115 VAC, full load		1.5	Sec.
	277 VAC, full load		1.0	Sec.

**Output Specifications**

Parameters	Conditions	Typical	Maximum	Units
Current accuracy		±5		%
Line regulation	LL to HL	±3		%
Load regulation	Full Output Voltage Range	±5		%
Ripple & Noise			2.5	V p-p
Output Current Ripple	Full load, 16.7-20ms duration		1.5	A p-p
Current Overshoot	LL to HL, full load at cold start, % of rated output current		10	%
Hold-up time (min)			0	ms
Minimum Load Voltage		See Models Table Above		

**Isolation Specifications**

Parameters	Conditions	Typical	Rated	Units
Tested I/O voltage	I/P – O/P		3750	VAC
	I/P – FG		2000	
	O/P – FG		500	
Isolation Resistance	I/P – O/P, 500Vdc	>100MΩ		VAC
Isolation Capacitance			2500	pF

**General Specifications**

Parameters	Conditions	Typical	Maximum	Units
Switching frequency		150		KHz
Over voltage protection			50	VDC
Short circuit protection		Hiccup Mode		
Short circuit restart		Auto Recovery		

Open circuit protection	Hiccup Mode		
Operating temperature	With Derating over °C	-40 to +60	°C
Storage temperature		-40 to +90	
Maximum case temperature		90	°C
Temperature coefficient		0.03	% / °C
Cooling	Free Air Convection		
Humidity		90	% RH
Case material	Metal (Aluminum)		
Potting material	Epoxy (IP67 rated)		
IP Rating	IP67		
Weight	430		g
Dimensions (L X W+ X H)	6.50 X 1.91 X 1.31 inches	165 X 48.6 X 33.3 mm	
MTBF	400,000 hrs (MIL-HDBK-217F at +25°C)		

## Safety Specifications


Parameters	
Agency Approvals	NOM (for all part numbers with *)
	Electromagnetic Interference EN55015 / FCC Part 15, Class B
	Harmonic Current Emissions EN61000-3-2, Class B
	Voltage fluctuations and flicker EN61000-3-3
	Electrostatic Discharge Immunity EN61000-4-2, 8kV Air, 4kV Contact, Level 3, Criteria A
	RF, Electromagnetic Field Immunity EN61000-4-3, Test-RS Level 3, Criteria A
Standards	Electrical Fast Transient / Burst Immunity EN61000-4-4, Burst EFT Level 3, Criteria A
	Surge Immunity EN61000-4-5, Line to Neutral 4kV, Line/Neutral to FG 6kV
	RF, Conducted Disturbance Immunity EN61000-4-6, Test-CS Level 3, Criteria A
	Power frequency Magnetic Field Immunity EN61000-4-8, Test 3A/m, Criteria A
	Voltage dips, Short Interruptions Immunity EN61000-4-11, Criteria B
	Electromagnetic Immunity Requirements Applies to Lighting Equipment EN61547

## Pin Definition


Wire	Connection
Brown	AC L
Blue	AC N
Yellow/Green	FG
Red	+V Output
Black	-V Output

## Dimensions


### Top View



### Side View




## Application Block diagram




## Efficiency Vs. Input Voltage &amp; Output Voltage

AMER40-4275Z




AMER40-4290Z




## PF vs. Input Voltage & Output Voltage

AMER40-4275Z



AMER40-4290Z



**NOTE:** 1. Datasheets are updated as needed and as such, specifications are subject to change without notice. Once printed or downloaded, datasheets are no longer controlled by Aimtec; refer to [www.aimtec.com](http://www.aimtec.com) for the most current product specifications. 2. Product labels shown, including safety agency certifications on labels, may vary based on the date manufactured. 3. Mechanical drawings and specifications are for reference only. 4. All specifications are measured at an ambient temperature of 25°C, humidity<75%, nominal input voltage and at rated output load unless otherwise specified. 5. Aimtec may not have conducted destructive testing or chemical analysis on all internal components and chemicals at the time of publishing this document. CAS numbers and other limited information are considered proprietary and may not be available for release. 6. This product is not designed for use in critical life support systems, equipment used in hazardous environments, nuclear control systems or other such applications which necessitate specific safety and regulatory standards other the ones listed in this datasheet. 7. Warranty is in accordance with Aimtec's standard Terms of Sale available at [www.aimtec.com](http://www.aimtec.com).