


Inductive Sensors
BES M08EG-PSC15A-S49G-W
Order Code: BES02YR



Basic features

Additional features	Factor 1 Weld immune
Approval/Conformity	CE WEEE
Basic standard	IEC 60947-5-2
Trademark	Factor 1

Display/Operation

Function indicator	yes
Power indicator	no

Electrical connection

Connection	M8x1-Male, 3-pin
Polarity reversal protected	yes
Protection against device mix-ups	yes
Short-circuit protection	yes

Electrical data

Load capacitance max. at Ue	1 µF
Magnetic field strength, interference field	100 kA/m
Min. operating current Im	0 mA
No-load current Io max., damped	15 mA
No-load current Io max., undamped	15 mA
Operating voltage Ub	10...30 VDC
Rated insulation voltage Ui	75 V DC
Rated operating current Ie	150 mA
Rated operating voltage Ue DC	24 V
Rated short circuit current	100 A
Ready delay tv max.	15 ms
Residual current Ir max.	80 µA
Ripple max. (% of Ue)	10 %
Switching frequency	2000 Hz
Utilization category	DC -13
Voltage drop static max.	2.5 V

Environmental conditions

Ambient temperature	-25...70 °C
Contamination scale	3
EN 60068-2-27, Shock	Half-sinus, 30 gn, 11 ms
EN 60068-2-6, Vibration	55 Hz, amplitude 1 mm, 3x30 min
IP rating	IP67
Magnetic field immune	magnetic field immune (AC/DC)

Interface

Switching output	PNP normally open (NO)
------------------	------------------------

Inductive Sensors
BES M08EG-PSC15A-S49G-W
Order Code: BES02YR



Material

Housing material	1.4301 stainless steel, PTFE coated
Material sensing surface	PBT/PTFE

Mechanical data

Dimension	Ø 8 x 49 mm
Installation	for flush mounting
Mounting length	40.00 mm
Size	M8x1
Tightening torque	10 Nm

Range/Distance

Assured operating distance Sa	1.2 mm
Hysteresis H max. (% of Sr)	15.0 %
Rated operating distance Sn	1.5 mm
Real switching distance sr	1.5 mm
Repeat accuracy max. (% of Sr)	5.0 %
Temperature drift max. (% of Sr)	10 %
Tolerance Sr	±10 %

Remarks

EMC: For operating conditions with noise sources
External protection circuit is required. Document 825345.
The sensor is functional again after the overload has been eliminated.

Connector Drawings



Wiring Diagrams

