


Single-Ended Cordsets  
BKS-S 48-15-CP-02  
Order Code: BCC0069

# BALLUFF



## Basic features

Approval/Conformity	CE WEEE
---------------------	------------

## Electrical connection

Bending radius min., fixed cable	5 x D
Bending radius min., flexible cable	10 x D
Cable	PUR Shielded black, 2 m
Cable diameter D	4.50 mm ±0.20 mm
Conductor cross-section	0.34 mm <sup>2</sup>
Connection	M8x1-Female, straight, 3-pin, A-coded
Connector configuration	Straight
Number of conductors	2
Number of pins	3
System	Molded

## Electrical data

Operating voltage $U_b$	36 VDC / 30 VAC
Rated current (40 °C)	3.0 A

## Remarks

Enclosure rating per IEC 60529, only in screwed state with the associated mating piece.

## Environmental conditions

Ambient temperature	-25...90 °C
Cable temperature, fixed routing	-40...70 °C
Cable temperature, flexible routing	5...70 °C
IP rating	IP67


## Material

Cable jacket material, note	Shielded
Cable jacket, material	PUR
Material contact carrier	PUR
Material contacts	Bronze
Material cover nut	Brass
Material grip	PUR

## Mechanical data

Cable jacket, color	black
Cable length L	2.00 m
Tightening torque pigtail	0.4 Nm

## Connector Drawings



PIN 1: brown

PIN 3: blue

PIN 4: Shield