




Inductive Sensors
BES 517-132-U6-H
Order Code: BES023L



Basic features

Approval/Conformity	CE WEEE
Basic standard	IEC 60947-5-2

Display/Operation

Function indicator	yes
Power indicator	yes

Electrical connection

Polarity reversal protected	yes
Protection against device mix-ups	yes
Short-circuit protection	yes

Electrical data

Load capacitance max. at Ue	1 μ F
Min. operating current I _m	0 mA
No-load current I _o max., damped	20 mA
No-load current I _o max., undamped	15 mA
Operating voltage U _b	10...55 VDC
Output resistance R _a	33.0 kOhm + D
Protection class	II
Rated insulation voltage U _i	250 V AC
Rated operating current I _e	200 mA
Rated operating voltage U _e DC	24 V
Rated short circuit current	100 A
Ready delay t _v max.	30 ms
Residual current I _r max.	80 μ A
Ripple max. (% of U _e)	15 %
Switching frequency	50 Hz
Utilization category	DC -13
Voltage drop static max.	2.5 V

Inductive Sensors
BES 517-132-U6-H
Order Code: BES023L



Environmental conditions

Ambient temperature	-25...70 °C
Contamination scale	3
EN 60068-2-27, Shock	Half-sinus, 30 g _n , 11 ms
EN 60068-2-6, Vibration	55 Hz, amplitude 1 mm, 3x30 min
IP rating	IP67

Interface

Cable fitting, thread size	NPT 1/2"
Switching output	PNP normally open/normally closed (NO/NC)

Material

Housing material	Aluminium PBT
Material sensing surface	PBT

Mechanical data

Connection cross-section	2.5 mm ²
Dimension	120 x 40 x 40 mm
Installation	for flush mounting
Size	40x40
Tightening torque	4...5 Nm (NPT 1/2")
Tightening torque clamping screw	0.8 Nm

Range/Distance

Assured operating distance S _a	16 mm
Hysteresis H max. (% of S _r)	20.0 %
Rated operating distance S _n	20 mm
Real switching distance s _r	20 mm
Repeat accuracy max. (% of S _r)	5.0 %
Temperature drift max. (% of S _r)	10 %
Tolerance S _r	±10 %

Remarks

The sensor is functional again after the overload has been eliminated.
LED 1: Function
LED 2: Operating voltage

Wiring Diagrams

