




1) Reference edge, 2) Anti-crystallization plunger



Basic features

Operating principle 1. Switch position: Mechanical

Display/Operation

Function indicator 1. Switch position: None

Electrical connection

Connection	M12x1-Flange male, 5-pin
Connection type	1. Switch position: Connector

Electrical data

Continuous current	1. Switch position: 0.1 A
Rated operating voltage Ue	1. Switch position: 250 V AC
Switching rate	1. Switch position: 200/min

Environmental conditions

Ambient temperature	-5...85 °C
IP rating	IP67

Material

Housing material	Aluminium, Anodized
Housing material, surface protection	Anodized
Material contacts	1. Switch position: Gold
Plunger material	1. Switch position: 1.4034 stainless steel


Mechanical data

Approach direction	lateral or at right angles to mounting surface
Approach speed	1. Switch position: 10 m/min
Distance cam - reference edge	1. Switch position: 2.30...2.80 mm
Flange, feed-through	None
Installation	any
Life expectancy mechanical	1. Switch position: 10 mil. switching operations
Number of switching positions	E-chisel Mechanical
Plunger style	1st switch position: E-Chisel 1st switch position: E-Chisel
Switch actuation force	1. Switch position: 8 N
Switching element	1. Switch position: BSE 73.1

Range/Distance

Reproducibility 1. Switch position: ± 0.02 mm

Connector Drawings



View of connector side

Wiring Diagrams

