


Inductive Sensors  
BES M08EA-POD15B-S49G  
Order Code: BES0270

**BALLUFF**



1) Sensing surface



#### Basic features

|                     |                             |
|---------------------|-----------------------------|
| Approval/Conformity | CE<br>UKCA<br>cULus<br>WEEE |
| Basic standard      | IEC 60947-5-2               |

#### Display/Operation

|                    |    |
|--------------------|----|
| Function indicator | no |
| Power indicator    | no |

#### Electrical connection

|                                   |                  |
|-----------------------------------|------------------|
| Connection                        | M8x1-Male, 3-pin |
| Polarity reversal protected       | yes              |
| Protection against device mix-ups | yes              |
| Short-circuit protection          | yes              |

#### Electrical data

|                                               |                |
|-----------------------------------------------|----------------|
| Load capacitance max. at Ue                   | 0.2 $\mu$ F    |
| Min. operating current I <sub>m</sub>         | 1 mA           |
| No-load current I <sub>o</sub> max., damped   | 3 mA           |
| No-load current I <sub>o</sub> max., undamped | 9 mA           |
| Operating voltage U <sub>b</sub>              | 10...30 VDC    |
| Output resistance R <sub>a</sub>              | Open collector |
| Rated insulation voltage U <sub>i</sub>       | 75 V DC        |
| Rated operating current I <sub>e</sub>        | 150 mA         |
| Rated operating voltage U <sub>e</sub> DC     | 24 V           |
| Rated short circuit current                   | 100 A          |
| Ready delay t <sub>v</sub> max.               | 20 ms          |
| Residual current I <sub>r</sub> max.          | 10 $\mu$ A     |
| Ripple max. (% of U <sub>e</sub> )            | 10 %           |
| Switching frequency                           | 3000 Hz        |
| Utilization category                          | DC-13          |
| Voltage drop static max.                      | 2.5 V          |

#### Environmental conditions

|                         |                                       |
|-------------------------|---------------------------------------|
| Ambient temperature     | -25...70 °C                           |
| Contamination scale     | 3                                     |
| EN 60068-2-27, Shock    | Half-sinus, 30 g <sub>n</sub> , 11 ms |
| EN 60068-2-6, Vibration | 55 Hz, amplitude 1 mm, 3x30 min       |
| IP rating               | IP67                                  |

#### Functional safety

|              |       |
|--------------|-------|
| MTTF (40 °C) | 830 a |
|--------------|-------|

Interface

Switching output PNP normally closed (NC)

Material

Housing material Stainless steel

Material sensing surface PBT

Mechanical data

Dimension Ø 8 x 18 mm

Installation for flush mounting

Mounting length 10.90 mm

Size M8x1

Tightening torque 4 Nm

Range/Distance

Assured operating distance Sa 1.2 mm

Hysteresis H max. (% of Sr) 15.0 %

Rated operating distance Sn 1.5 mm

Real switching distance sr 1.5 mm

Repeat accuracy max. (% of Sr) 5.0 %

Temperature drift max. (% of Sr) 10 %

Tolerance Sr ±10 %

Remarks

For mounting and installation see Accessories section

EMC: EMC protection circuit required, see 825345. IVW: 2.2

The sensor is functional again after the overload has been eliminated.

For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

Connector Drawings



Wiring Diagrams

