




1) Reference edge, 2) 1st pos.



## Basic features

|                     |                                  |
|---------------------|----------------------------------|
| Approval/Conformity | CE<br>UKCA<br>CCC<br>WEEE        |
| Basic standard      | IEC 60947-5-1                    |
| Operating principle | 1-2. Switch position: Mechanical |
| Version             | Snap contact                     |

## Display/Operation

Function indicator 1-2. Switch position: None

## Electrical connection

Connection type 1-2. Switch position: Screw terminal

### Electrical data

|                                      |                                                                                      |
|--------------------------------------|--------------------------------------------------------------------------------------|
| <b>Continuous current</b>            | 1-2. Switch position: 6 A                                                            |
| <b>Rated operating voltage Ue</b>    | 1-2. Switch position: 250 V AC                                                       |
| <b>Switching function mechanical</b> | Double-interrupting<br>galvanically isolated<br>One NO and one NC<br>Dual changeover |
| <b>Switching rate</b>                | 1-2. Switch position: 300/min                                                        |

### Environmental conditions

|                     |            |
|---------------------|------------|
| Ambient temperature | -5...85 °C |
| IP rating           | IP67       |

## Functional safety

B10d (EN ISO 13849-1) BSE 30.0: 30 mil. switching cycles

## Material

|                                             |                                              |
|---------------------------------------------|----------------------------------------------|
| <b>Housing material</b>                     | Aluminium, Anodized                          |
| <b>Housing material, surface protection</b> | Anodized                                     |
| <b>Material contacts</b>                    | 1-2. Switch position: Silver, gold plated    |
| <b>Plunger material</b>                     | 1-2. Switch position: 1.4034 stainless steel |

## Mechanical data

|                                     |                                                    |
|-------------------------------------|----------------------------------------------------|
| Approach direction                  | Vertical to mounting surface                       |
| Approach speed                      | 1-2. Switch position: 60 m/min                     |
| Dimension                           | 84 x 90 x 77 mm                                    |
| Distance cam - reference edge       | 1-2. Switch position: 2.50...3.00 mm               |
| Flange, feed-through                | 1 threaded exit M25                                |
| Installation                        | Vertical                                           |
| Life expectancy mechanical          | 1-2. Switch position: 30 mil. switching operations |
| Number of switching positions       | 2x Roller Mechanical                               |
| Plunger spacing 1st switch position | 50 mm                                              |
| Plunger style                       | 1-2nd switch position: Roller                      |
| Switch actuation force              | 1-2. Switch position: 20 N                         |
| Switching element                   | 1-2. Switch position: BSE 30.0                     |

Range/Distance

Reproducibility  
Switch position spacing

1-2. Switch position:  $\pm 0.01$  mm  
12 mm

Wiring Diagrams

BSE 30.0

