

Bulkhead Connectors


BCC M424-E814-BG-RM013-000

Order Code: BCC085H











μ	CIO	feati	Iroc
	311.		11 (5.5)

Approval/Conformity WEEE

Display/Operation

Power indicator no/no

Electrical connection

Connection 1 M12x1-Female, angled, 4-pin, D-coded

Connection 2 RJ45-Female, straight, 4-pin

Connector 01, versionangledConnector 02, versionstraightNumber of pins4/4

Electrical data

Operating voltage Ub 60 VDC / 60 VAC Rated current (40 °C) 0.5 A

Environmental conditions

 $\begin{array}{lll} \mbox{Ambient temperature} & -20...80\ ^{\circ}\mbox{C} \\ \mbox{IP rating} & \mbox{IP67/IP20} \\ \end{array}$

Material

Material contact carrierPURMaterial contactsBrass/BrassMaterial gripPUR

Mechanical data

Mounting part M16x1.5

Remarks

Enclosure rating per IEC 60529 or 20653, only in mounted and screwed state with the associated mating piece.


Connector Drawings

BCC M424-E814-BG-RM013-000

Order Code: BCC085H



Wiring Diagrams



- 1) Shield on cover nut
- 2) Shield on housing

Subject to change without notice: 183244