





Mechanical Cam Switches
BNS 819-99-R-12
Order Code: BNS004Y



1) Reference edge



Basic features

Operating principle	1. Switch position: Mechanical
---------------------	--------------------------------

Display/Operation

Function indicator	1. Switch position: None
--------------------	--------------------------

Electrical connection

Connection type	1. Switch position: Solder connection
-----------------	---------------------------------------

Electrical data

Continuous current	1. Switch position: 0.1 A
Rated operating voltage U _e	1. Switch position: 250 V AC
Switching rate	1. Switch position: 200/min

Environmental conditions

Ambient temperature	-5...85 °C
IP rating	IP67

Material

Housing material	Aluminium, Anodized
Housing material, surface protection	Anodized
Material contacts	1. Switch position: Gold
Plunger material	1. Switch position: 1.4034 stainless steel

Mechanical data

Approach direction	lateral or at right angles to mounting surface
Approach speed	1. Switch position: 60 m/min
Dimension	40 x 20 x 43 mm
Distance cam - reference edge	1. Switch position: 2.30...2.80 mm
Flange, feed-through	None
Installation	any
Life expectancy mechanical	1. Switch position: 10 mil. switching operations
Number of switching positions	Roller Mechanical
Plunger spacing 1st switch position	10 mm
Plunger style	1st switch position: Roller 1st switch position: Roller
Switch actuation force	1. Switch position: 8 N
Switching element	1. Switch position: BSE 73.1

Range/Distance

Reproducibility	1. Switch position: ±0.05 mm
-----------------	------------------------------

Wiring Diagrams

