


Mechanical Cam Switches
BNS 819-99-K-10-FC-S80
Order Code: BNS041W



1) Reference edge, 2) Function indicator FC



Basic features

Operating principle	1. Switch position: Mechanical
---------------------	--------------------------------

Display/Operation

Function indicator	1. Switch position: FC - 6...24 V
--------------------	-----------------------------------

Electrical connection

Connection	M12x1-Flange male, 5-pin
Connection type	1. Switch position: Connector

Electrical data

Continuous current	1. Switch position: 4 A
Rated operating voltage Ue	1. Switch position: 24 V DC
Switching rate	1. Switch position: 200/min

Environmental conditions

Ambient temperature	-5...85 °C
IP rating	IP67

Material

Housing material	Aluminium, Anodized
Housing material, surface protection	Anodized
Material contacts	1. Switch position: Fine silver
Plunger material	1. Switch position: 1.4034 stainless steel


Mechanical data

Approach direction	longitudinal, parallel to attachment surface
Approach speed	1. Switch position: 9 m/min
Dimension	40 x 20 x 49 mm
Distance cam - reference edge	1. Switch position: 2.30...2.80 mm
Flange, feed-through	None
Installation	any
Life expectancy mechanical	1. Switch position: 10 mil. switching operations
Number of switching positions	Ball Mechanical
Plunger spacing 1st switch position	10 mm
Plunger style	1st switch position: Ball 1st switch position: Ball
Switch actuation force	1. Switch position: 8 N
Switching element	1. Switch position: BSE 69.1

Range/Distance

Reproducibility	1. Switch position: ±0.03 mm
-----------------	------------------------------

Connector Drawings



View of connector side

Wiring Diagrams

