


Inductive Sensors
BES 516-325-SA96-S4-W
Order Code: BES02J8



Basic features

Additional features	Weld immune
Approval/Conformity	cULus CE UKCA WEEE
Base type deviation	Ceramic coating
Basic standard	IEC 60947-5-2

Display/Operation

Function indicator	yes
Power indicator	no

Electrical connection

Connection	M12x1-Male, 4-pin, A-coded
Polarity reversal protected	yes
Protection against device mix-ups	yes
Short-circuit protection	yes

Electrical data

Load capacitance max. at Ue	1 μ F
Magnetic field strength, interference field	100 kA/m
Min. operating current I _m	0 mA
No-load current I _o max., damped	20 mA
No-load current I _o max., undamped	15 mA
Operating voltage U _b	10...30 VDC
Output resistance R _a	33.0 kOhm + D
Protection class	II
Rated insulation voltage U _i	250 V AC
Rated operating current I _e	200 mA
Rated operating voltage U _e DC	24 V
Rated short circuit current	100 A
Ready delay t _v max.	60 ms
Residual current I _r max.	80 μ A
Ripple max. (% of U _e)	10 %
Switching frequency	1000 Hz
Utilization category	DC -13
Voltage drop static max.	2.5 V

Environmental conditions

Ambient temperature	-25...70 °C
Contamination scale	3
EN 60068-2-27, Shock	Half-sinus, 30 g _n , 11 ms
EN 60068-2-6, Vibration	55 Hz, amplitude 1 mm, 3x30 min
IP rating	IP67
Magnetic field immune	magnetic field immune (AC/DC)

Functional safety

MTTF (40 °C)	740 a
--------------	-------

Interface

Switching output PNP normally open (NO)

Material

Housing material Brass, PTFE coated
Material sensing surface ceramic coated

Mechanical data

Dimension Ø 12 x 61 mm
Installation for flush mounting
Mounting length 40.00 mm
Size M12x1
Tightening torque 10 Nm

Range/Distance

Assured operating distance Sa 1.4 mm
Hysteresis H max. (% of Sr) 15.0 %
Rated operating distance Sn 2 mm
Real switching distance sr 2 mm
Repeat accuracy max. (% of Sr) 5.0 %
Temperature drift max. (% of Sr) 10 %
Tolerance Sr ±10 %

Remarks

For flush mounting: see installation instructions for inductive sensors with extended switching distance 825357. Sn: reduced by the coating thickness of 0.2 mm.

The sensor is functional again after the overload has been eliminated.

For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

Connector Drawings



Wiring Diagrams

