


Double-Ended Cordsets  
BCC M415-M413-3A-300-VX43T2-100  
Order Code: BCC0AFT



Basic features

|                     |                     |
|---------------------|---------------------|
| Approval/Conformity | CE<br>cULus<br>WEEE |
|---------------------|---------------------|

Electrical connection

|                         |                                        |
|-------------------------|----------------------------------------|
| Cable                   | PVC Yellow, 10 m                       |
| Cable diameter D        | 4.70 mm $\pm$ 0.13 mm                  |
| Conductor cross-section | 22 AWG                                 |
| Connection 1            | M12x1-Female, straight, 5-pin, A-coded |
| Connection 2            | M12x1-Male, straight, 3-pin, A-coded   |
| Number of conductors    | 3                                      |
| System                  | Molded/Molded                          |

Electrical data

|                             |                   |
|-----------------------------|-------------------|
| Cable rated voltage AC max. | 300 V             |
| Cable rated voltage DC max. | 300 V             |
| Operating voltage $U_b$     | 250 VDC / 250 VAC |
| Rated current (40 °C)       | 4.0 A             |

Environmental conditions

|                                     |                                     |
|-------------------------------------|-------------------------------------|
| Cable temperature, fixed routing    | -40...105 °C                        |
| Cable temperature, flexible routing | -5...105 °C                         |
| IP rating                           | IP67, IP68, IP69K/IP67, IP68, IP69K |

Material

|                          |                             |
|--------------------------|-----------------------------|
| Cable jacket, material   | PVC                         |
| Material contact carrier | PUR/PUR                     |
| Material contacts        | Bronze/Brass                |
| Material cover nut       | Die-cast zinc/Die-cast zinc |
| Material grip            | PUR/PUR                     |


Mechanical data

|                                         |                           |
|-----------------------------------------|---------------------------|
| Cable jacket, color                     | Yellow                    |
| Cable length L                          | 10.00 m                   |
| Horizontal travel permitted, drag chain | 5 m                       |
| Tightening torque pigtail               | 0.6 Nm/0.6 Nm             |
| Traverse speed max., drag chain         | 200 m/min                 |
| Vertical travel permitted, drag chain   | 2 m at 5 m/s <sup>2</sup> |

Remarks

Bulk cable approval per UL-AWM Style 2661 & CSA AWM I/II A/B  
Enclosure rating per IEC 60529 or 20653, only in screwed state with the associated mating piece.

Connector Drawings



- I  
PIN 1: brown  
PIN 2: not used  
PIN 3: blue  
PIN 4: black  
PIN 5: not used
- II  
PIN 1: brown  
PIN 3: blue  
PIN 4: black

Wiring Diagrams

