



Mechanical Cam Switches
BNS 813-D05-D12-62-10-02
Order Code: BNS01EW

BALLUFF



1) Reference edge, 2) Sealing ring, 3) Cable passage, 4) Mark. Safety switch position



Basic features

Approval/Conformity	CE UKCA CCC WEEE
Basic standard	IEC 60947-5-1
Operating principle	1-5. Switch position: Mechanical
Version	Safety EN 60204-1

Material

Housing material	Aluminium, Anodized
Housing material, surface protection	Anodized
Material contacts	1-2. Switch position: Silver 3-5. Switch position: Silver, gold plated
Plunger material	1-5. Switch position: 1.4034 stainless steel

Display/Operation

Function indicator	1-5. Switch position: None
--------------------	----------------------------

Electrical connection

Connection type	1-5. Switch position: Screw terminal
-----------------	--------------------------------------

Electrical data

Continuous current	1-5. Switch position: 6 A
Rated operating voltage Ue	1-5. Switch position: 250 V AC
Switching rate	1-5. Switch position: 300/min

Environmental conditions

Ambient temperature	-5...85 °C
IP rating	IP67

Functional safety

B10d (EN ISO 13849-1)	BSE 30.0: 30 mil. switching cycles BSE 61: 30 mil. switching cycles
-----------------------	--

Mechanical data

Approach direction	longitudinal, parallel to attachment surface
Approach speed	1-5. Switch position: 40 m/min
Dimension	120 x 96 x 64 mm
Distance cam - reference edge	1-5. Switch position: 4.50...5.00 mm
Flange, feed-through	2 threaded exit M20
Installation	Vertical
Life expectancy mechanical	1-5. Switch position: 30 mil. switching operations
Number of switching positions	5x Chisel Mechanical
Plunger spacing 1st switch position	30 mm
Plunger style	1-5. switch position: Chisel
Switch actuation force	1-2. Switch position: 15 N 3-5. Switch position: 20 N
Switching element	1-2. Switch position: BSE 61 3-5. Switch position: BSE 30.0


Range/Distance

Reproducibility
Switch position spacing

1-5. Switch position: ± 0.002 mm
12 mm

Wiring Diagrams

BSE 61



BSE 30.0

