


Mechanical Cam Switches  
BNS 813-FR-60-185  
Order Code: BNS002Y



1) Reference edge, 2) Mark. Safety switch position



Basic features

|                     |                                |
|---------------------|--------------------------------|
| DIN switch          | DIN 43693                      |
| Operating principle | 1. Switch position: Mechanical |
| Version             | Safety EN 60204-1              |

Display/Operation

|                    |                          |
|--------------------|--------------------------|
| Function indicator | 1. Switch position: None |
|--------------------|--------------------------|

Electrical connection

|                 |                                    |
|-----------------|------------------------------------|
| Connection type | 1. Switch position: Screw terminal |
|-----------------|------------------------------------|

Electrical data

|                            |                              |
|----------------------------|------------------------------|
| Continuous current         | 1. Switch position: 6 A      |
| Rated operating voltage Ue | 1. Switch position: 250 V AC |
| Switching rate             | 1. Switch position: 300/min  |

Environmental conditions

|                     |            |
|---------------------|------------|
| Ambient temperature | -5...85 °C |
| IP rating           | IP67       |

Material

|                                      |                                            |
|--------------------------------------|--------------------------------------------|
| Housing material                     | Aluminium, Anodized                        |
| Housing material, surface protection | Anodized                                   |
| Material contacts                    | 1. Switch position: Fine silver            |
| Plunger material                     | 1. Switch position: 1.4034 stainless steel |

Mechanical data

|                                     |                                                            |
|-------------------------------------|------------------------------------------------------------|
| Approach direction                  | Vertical to mounting surface                               |
| Approach speed                      | 1. Switch position: 60 m/min                               |
| Dimension                           | 74 x 28 x 61 mm                                            |
| Distance cam - reference edge       | 1. Switch position: 4.50...5.00 mm                         |
| Flange, feed-through                | None                                                       |
| Installation                        | any                                                        |
| Life expectancy mechanical          | 1. Switch position: 30 mil. switching operations           |
| Number of switching positions       | Roller Mechanical                                          |
| Plunger spacing 1st switch position | 14 mm                                                      |
| Plunger style                       | 1st switch position: Roller<br>1st switch position: Roller |
| Switch actuation force              | 1. Switch position: 15 N                                   |
| Switching element                   | 1. Switch position: BSE 61                                 |

Range/Distance

|                 |                              |
|-----------------|------------------------------|
| Reproducibility | 1. Switch position: ±0.01 mm |
|-----------------|------------------------------|

Wiring Diagrams

BSE 61

