



Mechanical Cam Switches
BNS 813-FL-60-183-FD
Order Code: BNS002H



1) Reference edge, 2) Function indicator FD/FE/LL, 3) Mark. Safety switch position



Basic features

DIN switch	DIN 43693
Operating principle	1. Switch position: Mechanical
Version	Safety EN 60204-1

Display/Operation

Function indicator	1. Switch position: FD - 6...60 V
--------------------	-----------------------------------

Electrical connection

Connection type	1. Switch position: Screw terminal
-----------------	------------------------------------

Electrical data

Continuous current	1. Switch position: 6 A
Rated operating voltage U _e	1. Switch position: 250 V AC
Switching rate	1. Switch position: 300/min

Environmental conditions

Ambient temperature	-5...85 °C
IP rating	IP67

Material

Housing material	Aluminium, Anodized
Housing material, surface protection	Anodized
Material contacts	1. Switch position: Fine silver
Plunger material	1. Switch position: 1.4034 stainless steel

Mechanical data

Approach direction	longitudinal, parallel to attachment surface
Approach speed	1. Switch position: 120 m/min
Distance cam - reference edge	1. Switch position: 4.50...5.00 mm
Flange, feed-through	None
Installation	any
Life expectancy mechanical	1. Switch position: 30 mil. switching operations
Number of switching positions	Roller bearing Mechanical
Plunger spacing 1st switch position	14 mm
Plunger style	1st switch position: Roller bearing 1st switch position: Roller bearing
Switch actuation force	1. Switch position: 15 N
Switching element	1. Switch position: BSE 61

Range/Distance

Reproducibility	1. Switch position: ±0.01 mm
-----------------	------------------------------

Wiring Diagrams

BSE 61

