




1) Reference edge, 2) Sealing ring, 3) Function indicator FD/FE/LL, 4) Cable passage



#### Basic features

|                     |                                  |
|---------------------|----------------------------------|
| Approval/Conformity | CE<br>UKCA<br>CCC<br>WEEE        |
| Basic standard      | IEC 60947-5-1                    |
| DIN switch          | DIN 43697                        |
| Operating principle | 1-2. Switch position: Mechanical |
| Version             | Snap contact                     |

#### Display/Operation

|                    |                                     |
|--------------------|-------------------------------------|
| Function indicator | 1-2. Switch position: FD - 6...60 V |
|--------------------|-------------------------------------|

#### Electrical connection

|                 |                                      |
|-----------------|--------------------------------------|
| Connection type | 1-2. Switch position: Screw terminal |
|-----------------|--------------------------------------|

#### Electrical data

|                               |                                                                                      |
|-------------------------------|--------------------------------------------------------------------------------------|
| Continuous current            | 1-2. Switch position: 6 A                                                            |
| Rated operating voltage Ue    | 1-2. Switch position: 250 V AC                                                       |
| Switching function mechanical | Double-interrupting<br>galvanically isolated<br>One NO and one NC<br>Dual changeover |
| Switching rate                | 1-2. Switch position: 300/min                                                        |

#### Environmental conditions

|                     |            |
|---------------------|------------|
| Ambient temperature | -5...85 °C |
| IP rating           | IP67       |

#### Functional safety

|                       |                                    |
|-----------------------|------------------------------------|
| B10d (EN ISO 13849-1) | BSE 30.0: 30 mil. switching cycles |
|-----------------------|------------------------------------|

#### Material

|                                      |                                              |
|--------------------------------------|----------------------------------------------|
| Housing material                     | Aluminium, Anodized                          |
| Housing material, surface protection | Anodized                                     |
| Material contacts                    | 1-2. Switch position: Silver, gold plated    |
| Plunger material                     | 1-2. Switch position: 1.4034 stainless steel |

#### Mechanical data

|                               |                                                    |
|-------------------------------|----------------------------------------------------|
| Approach direction            | longitudinal, parallel to attachment surface       |
| Approach speed                | 1-2. Switch position: 10 m/min                     |
| Distance cam - reference edge | 1-2. Switch position: 4.50...5.00 mm               |
| Flange, feed-through          | 2 threaded exit M25                                |
| Installation                  | Vertical                                           |
| Life expectancy mechanical    | 1-2. Switch position: 30 mil. switching operations |
| Number of switching positions | 2x Ball Mechanical                                 |
| Plunger style                 | 1-2nd switch position: Ball                        |
| Switch actuation force        | 1-2. Switch position: 20 N                         |
| Switching element             | 1-2. Switch position: BSE 30.0                     |

#### Range/Distance

|                 |                                 |
|-----------------|---------------------------------|
| Reproducibility | 1-2. Switch position: ±0.002 mm |
|-----------------|---------------------------------|

Wiring Diagrams

BSE 30.0

