


Photoelectric Sensors
BOS 18E-PA-RD21-S4
Order Code: BOS01KF

BALLUFF



1) Optical axis receiver, 2) Optical axis emitter

CE ECOLAB®



**UK
CA**

Basic features

Approval/Conformity	CE UKCA cULus Ecolab WEEE
Basic standard	IEC 60947-5-2
Principle of operation	Photoelectric sensor
Series	18E
Style	Cylinder Straight optics

Display/Operation

Adjuster	no
----------	----

Electrical connection

Connection	Connector, M12x1-Male, 4-pin
Contact, surface protection	Gold plated
Polarity reversal protected	yes
Protection against device mix-ups	yes
Short-circuit protection	yes

Electrical data

Load capacitance max. at Ue	0.1 μ F
No-load current I ₀ max. at Ue	40 mA
Operating voltage U _b	10...30 VDC
Rated insulation voltage U _i	75 V DC
Rated operating current I _e	100 mA
Rated operating voltage U _e DC	24 V
Ripple max. (% of U _e)	15 %
Switching frequency	400 Hz
Turn-off delay toff max.	1.25 ms
Turn-on delay ton max.	1.25 ms
Utilization category	DC-13
Voltage drop U _d max. at I _e	2.5 V

Environmental conditions

Ambient temperature	-25...70 °C
Contamination scale	3
EN 60068-2-27, Shock	Half-sinus, 30 g _n , 11 ms, 3x6
EN 60068-2-6, Vibration	Half-sinus, 100 g _n , 2 ms, 3x8000 10...55 Hz, amplitude 1 mm, 3x30 min
	10...2000 Hz, amplitude 1 mm, 30 gn, 3x5 h
IP rating	IP68/IP67
IP rating per DIN 40050	IPx9K

Functional safety

MTTF (40 °C)	537 a
--------------	-------

Interface

Switching output	PNP normally closed (NC) PNP normally open (NO) Pins 4-2
------------------	---

Material

Housing material	1.4404 stainless steel
Material sensing surface	Glass

Mechanical data

Dimension	Ø 18 x 75 mm
Mounting part	Nut M18x1
Tightening torque max.	40 Nm

Optical features

Ambient light max.	10000 Lux
Beam characteristic	Divergent
LED group per IEC 62471	Exempt Group
Light type	LED, red light
Principle of optical operation	Diffuse sensor, energetic
Switching function, optical	Light/dark switching
Wave length	640 nm

Range/Distance

Hysteresis H max. (% of Sr)	10.0 %
Range	250 mm
Rated operating distance Sn	250 mm
Temperature drift max. (% of Sr)	10 %

Remarks


The sensor is functional again after the overload has been eliminated.
Reference object (target): gray card, 200 x 200, 90 % remission, axial approach.
For additional information, refer to user's guide.
Order accessories separately.
For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

Connector Drawings



Wiring Diagrams



Opto Symbols

