




Basic features

|                     |                     |
|---------------------|---------------------|
| Approval/Conformity | CE<br>cULus<br>WEEE |
|---------------------|---------------------|

Electrical connection

|                                     |                                         |
|-------------------------------------|-----------------------------------------|
| Bending radius min., fixed cable    | 5 x D                                   |
| Bending radius min., flexible cable | 10 x D                                  |
| Cable                               | PUR black, 1.5 m, drag chain compatible |
| Cable diameter D                    | 4.30 mm ±0.20 mm                        |
| Cable, bending cycles min.          | 5 mil.                                  |
| Cable, torsion stress               | ±180°/m                                 |
| Conductor cross-section             | 0.34 mm²                                |
| Connection 1                        | M8x1-Female, straight, 3-pin, A-coded   |
| Connection 2                        | M12x1-Male, angled, 3-pin, A-coded      |
| Number of conductors                | 3                                       |
| System                              | Molded/Molded                           |

Electrical data

|                       |                 |
|-----------------------|-----------------|
| Operating voltage Ub  | 60 VDC / 60 VAC |
| Rated current (40 °C) | 4.0 A           |

Environmental conditions

|                                             |                               |
|---------------------------------------------|-------------------------------|
| Cable temperature UL max., fixed routing    | 80 °C                         |
| Cable temperature UL max., flexible routing | 80 °C                         |
| Cable temperature, drag chain               | -25...60 °C                   |
| Cable temperature, fixed routing            | -50...90 °C                   |
| Cable temperature, flexible routing         | -25...90 °C                   |
| IP rating                                   | IP67, IP69K/IP67, IP68, IP69K |

Material

|                          |                                                    |
|--------------------------|----------------------------------------------------|
| Cable jacket, material   | PUR                                                |
| Material contact carrier | PUR/PUR                                            |
| Material contacts        | Bronze/Brass                                       |
| Material cover nut       | Die-cast zinc or nickel plated brass/Die-cast zinc |
| Material grip            | PUR/PUR                                            |


Mechanical data

|                                         |                       |
|-----------------------------------------|-----------------------|
| Acceleration max., drag chain           | 5 m/s²                |
| Cable jacket, color                     | black                 |
| Cable length L                          | 1.50 m                |
| Cable properties                        | drag chain compatible |
| Horizontal travel permitted, drag chain | 5 m                   |
| Tightening torque pigtail               | 0.4 Nm/0.6 Nm         |
| Traverse speed max., drag chain         | 200 m/min             |
| Vertical travel permitted, drag chain   | 5 m                   |

Remarks

Cable construction acc. to UL-AWM Style 20549  
Halogen-free per DIN VDE 0472 Part 815  
Silicone-free  
Flame resistance acc. to IEC 60332-2  
Enclosure rating per IEC 60529 or 20653, only in screwed state with the associated mating piece.

Connector Drawings



Wiring Diagrams

