




Basic features

|                                     |                                         |
|-------------------------------------|-----------------------------------------|
| Approval/Conformity                 | CE<br>cULus<br>WEEE                     |
| Electrical connection               |                                         |
| Bending radius min., fixed cable    | 5 x D                                   |
| Bending radius min., flexible cable | 10 x D                                  |
| Cable                               | PUR black, 1.5 m, drag chain compatible |
| Cable diameter D                    | 4.70 mm ±0.20 mm                        |
| Cable, bending cycles min.          | 5 mil.                                  |
| Cable, torsion stress               | ±180°/m                                 |
| Conductor cross-section             | 0.34 mm <sup>2</sup>                    |
| Connection 1                        | M8x1-Female, straight, 4-pin, A-coded   |
| Connection 2                        | M8x1-Male, angled, 4-pin, A-coded       |
| Number of conductors                | 4                                       |
| System                              | Molded/Molded                           |

Electrical data

|                                  |                 |
|----------------------------------|-----------------|
| Operating voltage U <sub>b</sub> | 60 VDC / 60 VAC |
| Rated current (40 °C)            | 4.0 A           |

Environmental conditions

|                                             |                         |
|---------------------------------------------|-------------------------|
| Cable temperature UL max., fixed routing    | 80 °C                   |
| Cable temperature UL max., flexible routing | 80 °C                   |
| Cable temperature, drag chain               | -25...60 °C             |
| Cable temperature, fixed routing            | -50...90 °C             |
| Cable temperature, flexible routing         | -25...90 °C             |
| IP rating                                   | IP67, IP69K/IP67, IP69K |

Material

|                          |                                                                           |
|--------------------------|---------------------------------------------------------------------------|
| Cable jacket, material   | PUR                                                                       |
| Material contact carrier | PUR/PUR                                                                   |
| Material contacts        | Bronze/Brass                                                              |
| Material cover nut       | Die-cast zinc or nickel plated brass/Die-cast zinc or nickel plated brass |
| Material grip            | PUR/PUR                                                                   |

Mechanical data

|                                         |                       |
|-----------------------------------------|-----------------------|
| Acceleration max., drag chain           | 5 m/s <sup>2</sup>    |
| Cable jacket, color                     | black                 |
| Cable length L                          | 1.50 m                |
| Cable properties                        | drag chain compatible |
| Horizontal travel permitted, drag chain | 5 m                   |
| Tightening torque pigtail               | 0.4 Nm/0.4 Nm         |
| Traverse speed max., drag chain         | 200 m/min             |
| Vertical travel permitted, drag chain   | 5 m                   |

Remarks

Cable construction acc. to UL-AWM Style 20549  
Halogen-free per DIN VDE 0472 Part 815  
Silicone-free  
Flame-retarding acc. to IEC 60332-2  
Enclosure rating per IEC 60529 or 20653, only in screwed state with the associated mating piece.

Connector Drawings



II

I

Wiring Diagrams

