


Photoelectric Sensors
BOW B-3232-DU-C-S75
Order Code: BOW002T



1) Reference edge



Basic features

Additional features	Static switching output with automatic readjustment of the switching threshold Contamination compensation up to 60% intensity loss and reduced object resolution depending on degree of contamination.
---------------------	---

Approval/Conformity

Basic standard
Principle of operation
Series
Style

CE
UKCA
WEEE
IEC 60947-5-2
Optical window sensor
B
Frame

Photoelectric Sensors
BOW B-3232-DU-C-S75
Order Code: BOW002T

BALLUFF

Display/Operation

Adjuster	Potentiometer 270° (3x)
Display	Output function- LED yellow LED green: Power
Setting	Pulse extension (On/Off) Object resolution (3 levels) Light-on/dark-on

Electrical connection

Connection	Connector, M8x1-Male, 4-pin
Contact, surface protection	Gold plated
Polarity reversal protected	yes
Short-circuit protection	yes

Electrical data

Load capacitance max. at Ue	0.1 µF
No-load current I _o max. at Ue	250 mA
Operating voltage U _b	15...30 VDC
Rated insulation voltage U _i	75 V DC
Rated operating current I _e	200 mA
Rated operating voltage U _e DC	24 V
Ready delay t _v max.	300 ms
Residual current I _r max.	50 µA
Ripple max. (% of U _e)	15 %
Switching frequency	500 Hz
Turn-off delay t _{off} max.	1 ms
Turn-on delay t _{on} max.	1 ms
Voltage drop U _d max. at I _e	3.5 V

Environmental conditions

Ambient temperature	-10...55 °C
IP rating	IP65

Interface

Duration of time function	T = 50 ms
Switching output	NPN static normally open/ normally closed (NO/NC) PNP static normally open/ normally closed (NO/NC)
Time function	switch-off delay

Material

Housing material	Aluminium, anodized, black
Material sensing surface	PMMA
Surface protection	anodized, black

Mechanical data

Active window (PL x AL)	320 x 320 mm
Dimension	15 x 370 x 364 mm
Mounting part	Screw M6

Optical features

Ambient light max.	2000 Lux
Beam characteristic	Divergent
Light type	Infrared
Principle of optical operation	Through-beam sensor
Smallest part typ.	4.0 mm (resolution "High")
Switching function, optical	Light/dark switching
Wave length	880 nm

Remarks

Order accessories separately.
For additional information, refer to user's guide.
Do not route connection cable parallel to high voltage lines.
The sensor is functional again after the overload has been eliminated.


Connector Drawings



Photoelectric Sensors
BOW B-3232-DU-C-S75
Order Code: BOW002T



Wiring Diagrams



Opto Symbols

