


BPI 4M303P-5K-B0-KPX60-050

Order Code: BPI00C6

BALLUFF



1) Power green, 2) LED yellow for Signal 1 (NO), 3) Slot numbering



Basic features

Approval/Conformity	CE
	UKCA
	cULus
	WEEE
Scope of delivery	Part labels (11x)
	Cover cap (3x)

Display/Operation

Power indicator	Green LED
Switching function display	Yellow LED (4x)

Electrical connection

Bending radius min., fixed cable	7.5 x D
Bending radius min., flexible cable	15 x D
Cable	PUR black, 5 m, drag chain compatible
Cable diameter D	6.20 mm ±0.2 mm
Cable, bending cycles min.	2 mil.
Conductor cross-section	0.34 mm ² + 0.75 mm ²
Connection slots	4x M8x1-Female, 3-pin
Number of conductors	6

Electrical data

Isolation resistance	≥ 10 GOhm
Operating voltage U _b	10...30 VDC
Output current max.	3 A
Rated operating voltage U _e DC	24 V
Total current max.	8 A

Environmental conditions

Cable temperature, fixed routing	-40...80 °C
Cable temperature, flexible routing	-20...80 °C
IP rating	IP67, when threaded in

Material

Cable jacket, material	PUR
Housing material	PBT, GF
Material contact carrier	PBT
Material contacts	Bronze (CuSn6), nickel layer


Mechanical data

Acceleration max., drag chain	10 m/s ²
Cable jacket, color	black
Cable length L	5.00 m
Cable properties	drag chain compatible
Casting	yes
Dimension	91 x 30 x 23 mm
Horizontal travel permitted, drag chain	10 m at 10 m/s ²
Mounting part	M4 (2x)
Tightening torque	1.2 Nm ±0.2 (M4)
Tightening torque pigtail	0.4 Nm + 0.1 Nm (M8 connector)
Traverse speed max., drag chain	3 m/s

Remarks

Cable construction acc. to UL-AWM Style 20549/10493
 Flame resistance per IEC 60332-1-2
 Flame resistance per UL 758/1581 FT2
 Oil resistant per DIN EN 60811-404 (VDE 0473-811-404)
 Enclosure rating per IEC 60529, only in screwed state with the associated mating piece.

Connector Drawings



I/O ports

PIN 1: +24V

PIN 3: 0V

PIN 4: Normally open


Junction blocks

BPI 4M303P-5K-B0-KPX60-050

Order Code: BPI00C6

BALLUFF

Wiring Diagrams

-) blue 0.75 mm²+) brown 0.75 mm²

1) white

2) green

3) yellow

4) gray

I) LED green

II) LED yellow