


Junction blocks

BPI 8M304P-5K-B0-KP XK0-030

Order Code: BPI00EH

BALLUFF



1) Power green, 2) LED yellow for Signal 1 (NO), 3) LED yellow for Signal 2 (NC), 4) Slot numbering



Basic features

Approval/Conformity	CE UKCA cULus WEEE
Scope of delivery	Part labels (11x) Cover cap (5x)

Display/Operation

Power indicator	Green LED
Switching function display	Yellow LED (16x)

Electrical connection

Bending radius min., fixed cable	7.5 x D
Bending radius min., flexible cable	15 x D
Cable	PUR black, 3 m, drag chain compatible
Cable diameter D	8.80 mm ±0.25 mm
Cable, bending cycles min.	2 mil.
Conductor cross-section	0.34 mm² + 0.75 mm²
Connection slots	8x M8x1-Female, 4-pin
Number of conductors	18

Electrical data

Isolation resistance	≥ 10 GOhm
Operating voltage U _b	10...30 VDC
Output current max.	3 A
Rated operating voltage U _e DC	24 V
Total current max.	8 A

Environmental conditions

Cable temperature, fixed routing	-40...80 °C
Cable temperature, flexible routing	-20...80 °C
IP rating	IP67, when threaded in

Material

Cable jacket, material	PUR
Housing material	PBT, GF
Material contact carrier	PBT
Material contacts	Bronze (CuSn6), nickel layer

Mechanical data

Acceleration max., drag chain	10 m/s²
Cable jacket, color	black
Cable length L	3.00 m
Cable properties	drag chain compatible
Casting	yes
Dimension	135 x 30 x 23 mm
Horizontal travel permitted, drag chain	10 m at 10 m/s²
Mounting part	M4 (2x)
Tightening torque	1.2 Nm ±0.2 (M4)
Tightening torque pigtail	0.4 Nm + 0.1 Nm (M8 connector)
Traverse speed max., drag chain	3 m/s

Junction blocks

BPI 8M304P-5K-B0-KPXK0-030

Order Code: BPI00EH

BALLUFF

Remarks

Cable construction acc. to UL-AWM Style 20549/10493


Flame resistance per IEC 60332-1-2

Flame resistance per UL 758/1581 FT2

Oil resistant per DIN EN 60811-404 (VDE 0473-811-404)

Enclosure rating per IEC 60529, only in screwed state with the associated mating piece.

Connector Drawings



I/O ports

PIN 1: +24V

PIN 2: Normally closed

PIN 3: 0V

PIN 4: Normally open


Junction blocks

BPI 8M304P-5K-B0-KPXK0-030

Order Code: BPI00EH

BALLUFF

Wiring Diagrams

-) blue 0.75 mm²+) brown 0.75 mm²

1) white

2) gray/pink

3) green

4) red/blue

5) yellow

6) white/green

7) gray

8) brown/green

9) pink

I) LED green

10) white/yellow

11) red

12) yellow/brown

13) black

14) white/gray

15) violet

16) gray/brown

II) LED yellow