


Inductive Sensors  
BES M05EB1-NOC08B-S26G  
Order Code: BES0508



1) Sensing surface



Basic features

|                     |                             |
|---------------------|-----------------------------|
| Approval/Conformity | cULus<br>CE<br>UKCA<br>WEEE |
| Basic standard      | IEC 60947-5-2               |

Display/Operation

|                    |     |
|--------------------|-----|
| Function indicator | yes |
| Power indicator    | no  |

Electrical connection

|                                   |             |
|-----------------------------------|-------------|
| Connection                        | M5x0.5-Male |
| Polarity reversal protected       | yes         |
| Protection against device mix-ups | yes         |
| Short-circuit protection          | yes         |

Electrical data

|                                   |             |
|-----------------------------------|-------------|
| Load capacitance max. at Ue       | 1 µF        |
| Min. operating current Im         | 0 mA        |
| No-load current Io max., damped   | 2 mA        |
| No-load current Io max., undamped | 6 mA        |
| Operating voltage Ub              | 10...30 VDC |
| Output resistance Ra              | open source |
| Rated insulation voltage Ui       | 75 V DC     |
| Rated operating current Ie        | 100 mA      |
| Rated operating voltage Ue DC     | 24 V        |
| Rated short circuit current       | 100 A       |
| Ready delay tv max.               | 21 ms       |
| Residual current Ir max.          | 10 µA       |
| Ripple max. (% of Ue)             | 10 %        |
| Switching frequency               | 5000 Hz     |
| Utilization category              | DC -13      |
| Voltage drop static max.          | 2 V         |

Environmental conditions

|                         |                                 |
|-------------------------|---------------------------------|
| Ambient temperature     | -25...70 °C                     |
| Contamination scale     | 3                               |
| EN 60068-2-27, Shock    | Half-sinus, 30 gn, 11 ms        |
| EN 60068-2-6, Vibration | 55 Hz, amplitude 1 mm, 3x30 min |
| IP rating               | IP67                            |

Functional safety

|              |       |
|--------------|-------|
| MTTF (40 °C) | 830 a |
|--------------|-------|

Inductive Sensors  
BES M05EB1-NOC08B-S26G  
Order Code: BES0508



Interface

Switching output NPN normally closed (NC)

Material

Housing material Stainless steel  
Material sensing surface PBT

Mechanical data

Dimension Ø 5 x 29 mm  
Installation for flush mounting  
Mounting length 16.5 mm  
Size M5x0.5  
Tightening torque 1 Nm

Range/Distance

Assured operating distance Sa 0.65 mm  
Hysteresis H max. (% of Sr) 15.0 %  
Rated operating distance Sn 0.8 mm  
Real switching distance sr 0.8 mm  
Repeat accuracy max. (% of Sr) 5.0 %  
Switching distance marking ■  
Temperature drift max. (% of Sr) 10 %  
Tolerance Sr ±10 %

Remarks

The sensor is functional again after the overload has been eliminated.  
For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

Connector Drawings



Wiring Diagrams

