


Inductive Sensors
BES G04EC-NSC15B-S26G
Order Code: BES011Z



1) Sensing surface



Basic features

Approval/Conformity	cULus CE UKCA WEEE
Basic standard	IEC 60947-5-2

Display/Operation

Function indicator	yes
Power indicator	no

Electrical connection

Connection	M5x0.5-Male
Polarity reversal protected	yes
Protection against device mix-ups	yes
Short-circuit protection	yes

Electrical data

Load capacitance max. at Ue	1 µF
Min. operating current Im	0 mA
No-load current Io max., damped	6 mA
No-load current Io max., undamped	2 mA
Operating voltage Ub	10...30 VDC
Output resistance Ra	open source
Rated insulation voltage Ui	75 V DC
Rated operating current Ie	100 mA
Rated operating voltage Ue DC	24 V
Rated short circuit current	100 A
Ready delay tv max.	21 ms
Residual current Ir max.	10 µA
Ripple max. (% of Ue)	10 %
Switching frequency	5000 Hz
Utilization category	DC -13
Voltage drop static max.	2 V

Environmental conditions

Ambient temperature	-25...70 °C
Contamination scale	3
EN 60068-2-27, Shock	Half-sinus, 30 gn, 11 ms
EN 60068-2-6, Vibration	55 Hz, amplitude 1 mm, 3x30 min
IP rating	IP67

Functional safety

MTTF (40 °C)	830 a
--------------	-------

Interface		Range/Distance	
Switching output	NPN normally open (NO)	Assured operating distance Sa	1.21 mm
Material		Hysteresis H max. (% of Sr)	15.0 %
Housing material	Stainless steel	Rated operating distance Sn	1.5 mm
Material sensing surface	PBT	Real switching distance sr	1.5 mm
Mechanical data		Repeat accuracy max. (% of Sr)	5.0 %
Dimension	Ø 4 x 29 mm	Switching distance marking	■ ■
Installation	for flush mounting	Temperature drift max. (% of Sr)	10 %
Mounting length	21.00 mm	Tolerance Sr	±10 %
Size	D4.0		

Remarks

The sensor is functional again after the overload has been eliminated.
For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

Connector Drawings



Wiring Diagrams

