



Basic features

|                     |                     |
|---------------------|---------------------|
| Approval/Conformity | CE<br>cULus<br>WEEE |
|---------------------|---------------------|

Display/Operation

|                            |            |
|----------------------------|------------|
| Function indicator (Pin 4) | LED yellow |
| Power indicator            | Green LED  |

Electrical connection

|                                     |                                        |
|-------------------------------------|----------------------------------------|
| Bending radius min., fixed cable    | 5 x D                                  |
| Bending radius min., flexible cable | 10 x D                                 |
| Cable                               | TPE Yellow, 2 m, drag chain compatible |
| Cable diameter D                    | 5.30 mm ±0.13 mm                       |
| Cable, bending cycles min.          | 10 mil.                                |
| Conductor cross-section             | 22 AWG                                 |
| Connection                          | M12x1-Female, straight, 5-pin, A-coded |
| Connector configuration             | Straight                               |
| Number of conductors                | 4                                      |
| Number of pins                      | 5                                      |
| System                              | Molded                                 |

Electrical data

|                             |        |
|-----------------------------|--------|
| Cable rated voltage AC max. | 300 V  |
| Cable rated voltage DC max. | 300 V  |
| Operating voltage Ub        | 30 VDC |
| Rated current (40 °C)       | 4.0 A  |

Environmental conditions

|                                     |                   |
|-------------------------------------|-------------------|
| Cable temperature, fixed routing    | -50...105 °C      |
| Cable temperature, flexible routing | -25...105 °C      |
| IP rating                           | IP67, IP68, IP69K |

Interface

|                  |                      |
|------------------|----------------------|
| Switching output | NPN NO/NC antivalent |
|------------------|----------------------|

Material

|                          |               |
|--------------------------|---------------|
| Cable jacket, material   | TPE           |
| Material contact carrier | PUR           |
| Material contacts        | Bronze        |
| Material cover nut       | Die-cast zinc |
| Material grip            | PUR           |

Mechanical data

|                           |                       |
|---------------------------|-----------------------|
| Cable jacket, color       | Yellow                |
| Cable length L            | 2.00 m                |
| Cable properties          | drag chain compatible |
| Tightening torque pigtail | 0.6 Nm                |


#### Remarks

Cable construction acc. to UL-AWM Style 20327

Flame resistance acc. to IEC 332-2

Enclosure rating per IEC 60529 or 20653, only in screwed state with the associated mating piece.

#### Connector Drawings




PIN 1: brown

PIN 2: white

PIN 3: blue

PIN 4: black

#### Wiring Diagrams



1) Green LED = Power

2) Yellow LED = Function