



Inductive Sensors
BES M08MH1-NSC30B-S04G
Order Code: BES02W7



Display/Operation

Power indicator	no
-----------------	----

Electrical connection

Connection	M12x1-Male, 4-pin, A-coded
Polarity reversal protected	yes
Protection against device mix-ups	no
Short-circuit protection	yes

Electrical data

Load capacitance max. at Ue	1 μ F
No-load current Io max., damped	11 mA
No-load current Io max., undamped	7 mA
Operating voltage Ub	10...30 VDC
Output resistance Ra	100.0 kOhm
Protection class	II
Rated insulation voltage Ui	250 V AC
Rated operating current Ie	200 mA
Rated operating voltage Ue DC	24 V
Rated short circuit current	100 A
Ready delay tv max.	40 ms
Residual current Ir max.	10 μ A
Ripple max. (% of Ue)	10 %
Switching frequency	1200 Hz
Voltage drop static max.	1.5 V

Environmental conditions

Ambient temperature	-25...70 °C
Contamination scale	3
IP rating	IP68

Functional safety

MTTF (40 °C)	584 a
--------------	-------

Interface

Switching output	NPN normally open (NO)
------------------	------------------------

Material

Housing material	Brass, Nickel-free coated
Material sensing surface	PBT

Mechanical data

Dimension	$\varnothing$ 8 x 63 mm
Installation	for flush mounting
Mounting length	43 mm
Size	M8x1

Range/Distance

Assured operating distance Sa	2.4 mm
Hysteresis H max. (% of Sr)	15.0 %
Rated operating distance Sn	3 mm
Real switching distance sr	3 mm
Repeat accuracy max. (% of Sr)	5.0 %
Switching distance marking	■■■
Temperature drift max. (% of Sr)	10 %
Tolerance Sr	$\pm$ 10 %

Connector Drawings



Wiring Diagrams

