



1) Sensing surface, 2) Metal plate



Basic features

Additional features	Factor 1
Approval/Conformity	CE UKCA cULus WEEE
Basic standard	IEC 60947-5-2
Trademark	Factor 1

Display/Operation

Function indicator	yes
Power indicator	yes

Electrical connection

Connection	M12x1-Male, 4-pin, A-coded
Polarity reversal protected	yes
Protection against device mix-ups	yes
Short-circuit protection	yes

Electrical data

Load capacitance max. at U_e	1 μ F
Magnetic field strength, interference field	100 kA/m
Min. operating current I_m	0 mA
No-load current I_0 max., damped	20 mA
No-load current I_0 max., undamped	15 mA
Operating voltage U_b	10...30 VDC
Output resistance R_o	33.0 kOhm + D
Protection class	II
Rated insulation voltage U_i	250 V AC
Rated operating current I_e	200 mA
Rated operating voltage U_e DC	24 V
Rated short circuit current	100 A
Ready delay t_v max.	30 ms
Residual current I_r max.	80 μ A
Ripple max. (% of U_e)	15 %
Switching frequency	250 Hz
Utilization category	DC-13
Voltage drop static max.	2.5 V

Environmental conditions

Ambient temperature	-10...60 °C
Contamination scale	3
EN 60068-2-27, Shock	Half-sinus, 30 g _n , 11 ms
EN 60068-2-6, Vibration	55 Hz, amplitude 1 mm, 3x30 min
IP rating	IP67
Magnetic field immune	magnetic field immune (AC/DC)

Functional safety

MTTF (40 °C) 785 a

Interface

Switching output PNP normally open (NO)

Material

Housing material PBT

Material sensing surface PBT

Mechanical data

Dimension 40 x 40 x 62 mm

Installation Flush on one side

Size 40x40

Range/Distance

Assured operating distance Sa 28.4 mm

Hysteresis H max. (% of Sr) 15.0 %

Rated operating distance Sn 35 mm

Real switching distance sr 35 mm

Repeat accuracy max. (% of Sr) 5.0 %

Temperature drift max. (% of Sr) 10 %

Tolerance Sr ±10 %

Remarks

LED 1: Function

LED 2: Operating voltage

The sensor is functional again after the overload has been eliminated.

Installed non-flush. For installation conditions see Instruction 939225.

Switching distance and tolerance data apply to the sensing surface location shown.

Installation: The sensor front edge must protrude at least 10 mm over metallic installation materials.

Sensor does not respond to loose aluminum chips on the sensing surface.

For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

Connector Drawings



Wiring Diagrams

