


Inductive Sensors
BES M12EG2-PSC20B-BV02-EXF
Order Code: BES05M3



Basic features

Approval/Conformity	CE IECEX ATEX WEEE
Basic standard	EN 60079-0 EN 60079-18 IEC 60947-5-2
Ex marking	ATEX: II 3G Ex ec IIC T6 Gc II 3D Ex tc IIIC T75 °C Dc IECEX: Ex ec IIC T6 Gc Ex tc IIIC T75 °C Dc

Electrical connection

Cable length L	2 m
Conductor cross-section	0.34 mm²
Connection type	Cable, 2 m, PUR
Polarity reversal protected	yes
Short-circuit protection	yes

Electrical data

Operating voltage Ub	10...30 VDC
Switching frequency	180 Hz

Environmental conditions

Ambient temperature	-5...60 °C
IP rating	IP67

Functional safety

MTTF (40 °C)	860 a
--------------	-------

Interface

Switching output	PNP normally open (NO)
------------------	------------------------

Material

Housing material	Stainless steel
Material jacket	PUR
Material sensing surface	Stainless steel

Mechanical data

Dimension	Ø 12 x 59 mm
Installation	for flush mounting
Mounting length	39.00 mm
Size	M12x1
Tightening torque	10 Nm

Range/Distance

Rated operating distance Sn	2 mm
-----------------------------	------

Wiring Diagrams

