


Double-Ended Cordsets  
BCC M414-E894-8G-672-ES34N9-003  
Order Code: BCC0K4C



Basic features

|                     |                     |
|---------------------|---------------------|
| Application         | Ethernet            |
| Approval/Conformity | CE<br>cULus<br>WEEE |

Electrical connection

|                                     |                                                   |
|-------------------------------------|---------------------------------------------------|
| Bending radius min., flexible cable | 10 x D                                            |
| Cable                               | TPE Shielded Orange, 0.3 m, drag chain compatible |
| Cable diameter D                    | 6.70 mm ±0.25 mm                                  |
| Cable, bending cycles min.          | 10 mil.                                           |
| Cable, note                         | Ethernet, CAT 5E                                  |
| Conductor cross-section             | 24 AWG                                            |
| Connection 1                        | M12x1-Male, straight, 4-pin, D-coded              |
| Connection 2                        | RJ45-Male, straight, 4-pin                        |
| Number of conductors                | 4                                                 |
| System                              | Molded/assembled                                  |

Electrical data

|                             |                    |
|-----------------------------|--------------------|
| Cable rated voltage AC max. | 600 V              |
| Cable rated voltage DC max. | 600 V              |
| Conductor construction      | 2x2 twisted-pair   |
| Conductor resistance        | ≤ 26.0 Ohm/1000 ft |
| Coupling resistance max.    | 100 Ohm ±15 Ohm    |
| Operating capacitance       | 13.5 pF/ft         |
| Operating voltage Ub        | 42 VDC / 30 VAC    |
| Rated current (40 °C)       | 1.0 A              |
| Transfer rate               | 10/100 Mbit/s      |

Environmental conditions

|                                     |             |
|-------------------------------------|-------------|
| Cable temperature, flexible routing | -40...80 °C |
| IP rating                           | IP67/IP20   |

Material

|                             |                                    |
|-----------------------------|------------------------------------|
| Cable jacket material, note | Shielded                           |
| Cable jacket, material      | TPE                                |
| Cable shield                | Aluminum foil and copper braid     |
| Material contact carrier    | PUR/PBT                            |
| Material contacts           | Brass/Phosphor bronze, gold plated |
| Material cover nut          | Brass<br>nickel-plated             |
| Material grip               | PUR/PVC                            |

Mechanical data


|                           |                       |
|---------------------------|-----------------------|
| Cable jacket, color       | Orange                |
| Cable length L            | 0.30 m                |
| Cable properties          | drag chain compatible |
| Tightening torque pigtail | 0.6 Nm/-              |

## Remarks

Cable construction acc. to UL CMX Outdoor or AWM Style 2463

Enclosure rating per IEC 60529 or ISO 20653, only in screwed state with the associated mating piece.

## Connector Drawings



II

PIN 1: white/orange

PIN 2: orange

PIN 3: white/green


PIN 4: not used

PIN 5: not used

PIN 6: green

PIN 7: not used

PIN 8: not used



I


PIN 1: white/orange

PIN 2: white/green

PIN 3: orange

PIN 4: green

## Wiring Diagrams



1) Shield on cover nut

2) Shield on housing