


1) Reference edge



Basic features

Operating principle	1. Switch position: Mechanical
Version	Snap contact

Display/Operation

Function indicator 1. Switch position: None

Electrical connection

Connection type 1. Switch position: Solder connection

Electrical data

Continuous current	1. Switch position: 5 A
Rated operating voltage Ue	1. Switch position: 250 V AC
Switching function mechanical	Single-pin changeover
Switching rate	1. Switch position: 200/min

Environmental conditions

Ambient temperature	-5...150 °C
IP rating	IP67

Functional safety

B10d (EN ISO 13849-1) BSE 79: 10 mil. switching cycles

Material

Housing material	Aluminium, Anodized
Housing material, surface protection	Anodized
Material contacts	1. Switch position: Fine silver
Plunger material	1. Switch position: 1.4034 stainless steel

Mechanical data

Approach direction	lateral or at right angles to mounting surface
Approach speed	1. Switch position: 9 m/min
Distance cam - reference edge	1. Switch position: 2.30...2.80 mm
Flange, feed-through	None
Installation	any
Life expectancy mechanical	1. Switch position: 10 mil. switching operations
Number of switching positions	Ball Mechanical
Plunger style	1st switch position: Ball 1st switch position: Ball
Switch actuation force	1. Switch position: 8 N
Switching element	1. Switch position: BSE 79

Range/Distance

Reproducibility 1. Switch position: ± 0.03 mm

Wiring Diagrams

