




1) Reference edge, 2) Mark. Safety switch position



Basic features

Approval/Conformity	CE UKCA CCC WEEE
Basic standard	IEC 60947-5-1
Operating principle	1-5. Switch position: Mechanical
Version	Safety EN 60204-1 Snap contact

Display/Operation

Function indicator 1-5. Switch position: None

Electrical connection

Connection type	1-5. Switch position: Screw terminal
-----------------	--------------------------------------

Electrical data

Continuous current	1-5. Switch position: 6 A
Rated operating voltage Ue	1-5. Switch position: 250 V AC
Switching function mechanical	Double-interrupting Dual changeover Normally open with snap funct. NC forced-opening per VDE galvanically isolated
Switching rate	1-4. Switch position: 160/min 5. Switch position: 300/min

Environmental conditions

Ambient temperature	-5...85 °C
IP rating	IP67

Functional safety

B10d (EN ISO 13849-1)	BSE 30.0: 30 mil. switching cycles
	BSE 85: 1 mil. switching cycles

Material

Housing material	Aluminium, Anodized
Housing material, surface protection	Anodized
Material contacts	1-4. Switch position: Silver 5. Switch position: Silver, gold plated
Plunger material	1-5. Switch position: 1.4034 stainless steel

Mechanical Cam Switches
BNS 813-B05-D12-61-A-20-04
Order Code: BNS0550



Mechanical data

Approach direction	longitudinal, parallel to attachment surface
Approach speed	1-5. Switch position: 40 m/min
Distance cam - reference edge	1-5. Switch position: 4.50...5.00 mm
Flange, feed-through	None
Installation	Vertical
Life expectancy mechanical	1-4. Switch position: 1 mil. switching operations 5. Switch position: 30 mil. switching operations

Number of switching positions	5x Chisel Mechanical
Plunger style	1-5. switch position: Chisel
Switch actuation force	1-4. Switch position: 30 N 5. Switch position: 20 N
Switching element	1-4. Switch position: BSE 85 5. Switch position: BSE 30.0

Range/Distance

Reproducibility	1-4. Switch position: ± 0.02 mm 5. Switch position: ± 0.002 mm
-----------------	---

Wiring Diagrams

