




1) Emitter



Basic features

Approval/Conformity	CE UKCA cULus WEEE
Basic standard	IEC 60947-5-2
Principle of operation	Photoelectric sensor
Reference receiver	BOS Q08M...-LE21-..
Series	Q08M
Style	Square Connection 90°

Display/Operation

Adjuster	no
----------	----

Electrical connection

Connection	Connector, M8x1-Male, 3-pin
Polarity reversal protected	yes

Electrical data

No-load current I _{o max.} at U _e	10 mA
Operating voltage U _b	10...30 VDC
Rated insulation voltage U _i	75 V DC
Rated operating voltage U _e DC	24 V
Ripple max. (% of U _e)	15 %

Environmental conditions

Ambient temperature	-5...55 °C
EN 60068-2-27, Shock	Half-sinus, 30 g _n , 11 ms, 3x6 Half-sinus, 100 g _n , 2 ms, 3x8000
EN 60068-2-6, Vibration	10...2000 Hz, 1 mm, 30 g _n , 3x5 h 10...55 Hz, amplitude 1 mm, 3x30 min
IP rating	IP67

Functional safety

MTTF (40 °C)	1579 a
--------------	--------

Material

Housing material	Zinc, Die casting, nickel-plated
Material sensing surface	PMMA
Surface protection	nickel-plated

Mechanical data

Dimension	8 x 59 x 8 mm
Mounting part	Screw M3

Optical features

Average power Po max.	390 µW
Beam characteristic	Divergent
Laser class per IEC 60825-1	1
Light spot size	Ø 3.0 mm Light exit
Light type	Laser red light
Principle of optical operation	Through-beam sensor (Emitter)
Pulse duration t max.	6 µs

Pulse frequency	8 kHz
Pulse power Pp max.	2 mW
Smallest part typ.	0.28 mm at 1 m. R0 = 3.0 m
Wave length	650 nm

Range/Distance

Range	0...3 m
Rated operating distance Sn	3 m

Remarks

Order accessories separately.

Only for applications per NFPA 79 (machines with a supply voltage of maximum 600 V). Use an R/C (CYJV2) cable with suitable properties for attaching the device.


For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

Connector Drawings



Wiring Diagrams



1) Emitter

Opto Symbols

