

1) Optical axis, 2) Output function, 3) Stability, 4) Sn



#### Basic features

Approval/Conformity	CE UKCA cULus WEEE
Basic standard	IEC 60947-5-2
Principle of operation	Photoelectric sensor
Series	18KW
Style	Flat cylinder Optics 90°
Trademark	Global

#### Display/Operation

Adjuster	Potentiometer 270°
Display	Output function- LED yellow Stability - LED green
Setting	Rated switching distance (Sn)

#### Electrical connection

Connection	Connector, M12x1-Male, 4-pin
Polarity reversal protected	yes
Short-circuit protection	yes

#### Electrical data

No-load current $I_0$ max. at $U_e$	35 mA
Operating voltage $U_b$	10...30 VDC
Rated insulation voltage $U_i$	75 V DC
Rated operating current $I_e$	100 mA
Rated operating voltage $U_e$ DC	24 V
Ripple max. (% of $U_e$ )	8 %
Switching frequency	1000 Hz
Turn-off delay $t_{off}$ max.	0.5 ms
Turn-on delay $t_{on}$ max.	0.5 ms
Voltage drop $U_d$ max. at $I_e$	2 V

#### Environmental conditions

Ambient temperature	-25...55 °C
EN 60068-2-27, Shock	Half-sinus, 30 g <sub>n</sub> , 11 ms, 3x6
EN 60068-2-6, Vibration	10...55 Hz, amplitude 0.5 mm, 3x30 min
IP rating	IP67

#### Functional safety

MTTF (40 °C)	774 a
--------------	-------

#### Interface

Switching output	PNP normally closed (NC) PNP normally open (NO) Pins 4-2
------------------	---

#### Material

Housing material	PBT
Material sensing surface	PMMA

#### Mechanical data

Dimension	Ø 18 x 93.5 mm
Mounting part	Screw M3 Nut M18x1
Tightening torque max.	1.5 Nm

#### Optical features

Ambient light max.	5000 Lux
Beam characteristic	Divergent
Light spot size	Ø 100 mm at 300 mm
Light type	LED infrared
Principle of optical operation	Diffuse sensor, energetic
Switching function, optical	Light-on
Wave length	880 nm

#### Range/Distance

Range	0...400 mm
Rated operating distance Sn	400 mm, Adjustable

#### Remarks


The sensor is functional again after the overload has been eliminated.  
Reference object (target): gray card, 200 x 200, 90 % remission, axial approach.  
For additional information, refer to user's guide.  
Order accessories separately.  
For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

#### Connector Drawings



#### Wiring Diagrams



#### Opto Symbols

