


Double-Ended Cordsets  
**BCC M425-M414-3A-606-PX0434-100**  
 Order Code: BCC071K

**BALLUFF**



#### Basic features

|                     |                     |
|---------------------|---------------------|
| Approval/Conformity | CE<br>cULus<br>WEEE |
|---------------------|---------------------|

#### Display/Operation

|                            |              |
|----------------------------|--------------|
| Function indicator (Pin 4) | LED yellow   |
| Power indicator            | LED green/no |

#### Electrical connection

|                                     |                                        |
|-------------------------------------|----------------------------------------|
| Bending radius min., fixed cable    | 5 x D                                  |
| Bending radius min., flexible cable | 10 x D                                 |
| Cable                               | PUR black, 10 m, drag chain compatible |
| Cable diameter D                    | 4.70 mm ±0.20 mm                       |
| Cable, bending cycles min.          | 5 mil.                                 |
| Cable, torsion stress               | ±180°/m                                |
| Conductor cross-section             | 0.34 mm²                               |
| Connection 1                        | M12x1-Female, angled, 5-pin, A-coded   |
| Connection 2                        | M12x1-Male, straight, 4-pin, A-coded   |
| Number of conductors                | 4                                      |
| System                              | Molded/Molded                          |

#### Electrical data

|                         |        |
|-------------------------|--------|
| Operating voltage $U_b$ | 30 VDC |
| Rated current (40 °C)   | 4.0 A  |

#### Environmental conditions

|                                             |                                     |
|---------------------------------------------|-------------------------------------|
| Cable temperature UL max., fixed routing    | 80 °C                               |
| Cable temperature UL max., flexible routing | 80 °C                               |
| Cable temperature, drag chain               | -25...60 °C                         |
| Cable temperature, fixed routing            | -50...90 °C                         |
| Cable temperature, flexible routing         | -25...90 °C                         |
| IP rating                                   | IP67, IP68, IP69K/IP67, IP68, IP69K |

#### Interface

|                  |                      |
|------------------|----------------------|
| Switching output | PNP NO/NC antivalent |
|------------------|----------------------|

#### Material

|                          |                             |
|--------------------------|-----------------------------|
| Cable jacket, material   | PUR                         |
| Material contact carrier | PUR/PUR                     |
| Material contacts        | Bronze/Brass                |
| Material cover nut       | Die-cast zinc/Die-cast zinc |
| Material grip            | PUR/PUR                     |


#### Mechanical data

|                                         |                       |
|-----------------------------------------|-----------------------|
| Acceleration max., drag chain           | 5 m/s²                |
| Cable jacket, color                     | black                 |
| Cable length L                          | 10.00 m               |
| Cable properties                        | drag chain compatible |
| Horizontal travel permitted, drag chain | 5 m                   |
| Tightening torque pigtail               | 0.6 Nm/0.6 Nm         |
| Traverse speed max., drag chain         | 200 m/min             |
| Vertical travel permitted, drag chain   | 5 m                   |


Remarks

Cable construction acc. to UL-AWM Style 20549  
Halogen-free per DIN VDE 0472 Part 815  
Silicone-free  
Flame-retarding acc. to IEC 60332-2  
Enclosure rating per IEC 60529 or 20653, only in screwed state with the associated mating piece.

Connector Drawings



Wiring Diagrams



- 1) Green LED = Power  
2) Yellow LED = Function