




## Basic features

|                     |                     |
|---------------------|---------------------|
| Approval/Conformity | CE<br>cULus<br>WEEE |
|---------------------|---------------------|

## Display/Operation

|                            |              |
|----------------------------|--------------|
| Function indicator (Pin 2) | LED white    |
| Function indicator (Pin 4) | LED yellow   |
| Power indicator            | LED green/no |

## Electrical connection

|                                     |                                        |
|-------------------------------------|----------------------------------------|
| Bending radius min., fixed cable    | 5 x D                                  |
| Bending radius min., flexible cable | 10 x D                                 |
| Cable                               | PVC gray, 0.3 m, drag chain compatible |
| Cable diameter D                    | 4.80 mm ±0.15 mm                       |
| Cable, bending cycles min.          | 2 mil.                                 |
| Conductor cross-section             | 0.34 mm <sup>2</sup>                   |
| Connection 1                        | M12x1-Female, angled, 5-pin, A-coded   |
| Connection 2                        | M12x1-Male, straight, 4-pin, A-coded   |
| Number of conductors                | 4                                      |
| System                              | Molded/Molded                          |

## Electrical data

|                                  |        |
|----------------------------------|--------|
| Operating voltage U <sub>b</sub> | 30 VDC |
| Rated current (40 °C)            | 4.0 A  |

## Environmental conditions

|                                             |                                     |
|---------------------------------------------|-------------------------------------|
| Cable temperature UL max., fixed routing    | 80 °C                               |
| Cable temperature UL max., flexible routing | 80 °C                               |
| Cable temperature, drag chain               | -5...60 °C                          |
| Cable temperature, fixed routing            | -40...105 °C                        |
| Cable temperature, flexible routing         | 5...105 °C                          |
| IP rating                                   | IP67, IP68, IP69K/IP67, IP68, IP69K |

## Interface

|                  |                      |
|------------------|----------------------|
| Switching output | PNP NO/NC antivalent |
|------------------|----------------------|

## Material

|                          |                             |
|--------------------------|-----------------------------|
| Cable jacket, material   | PVC                         |
| Material contact carrier | PUR/PUR                     |
| Material contacts        | Bronze/Brass                |
| Material cover nut       | Die-cast zinc/Die-cast zinc |
| Material grip            | PUR/PUR                     |


## Mechanical data

|                                         |                       |
|-----------------------------------------|-----------------------|
| Acceleration max., drag chain           | 5 m/s <sup>2</sup>    |
| Cable jacket, color                     | gray                  |
| Cable length L                          | 0.30 m                |
| Cable properties                        | drag chain compatible |
| Horizontal travel permitted, drag chain | 5 m                   |
| Tightening torque pigtail               | 0.6 Nm/0.6 Nm         |
| Traverse speed max., drag chain         | 200 m/min             |
| Vertical travel permitted, drag chain   | 2 m                   |

Remarks

Cable construction acc. to UL-AWM Style 2517  
Silicone-free  
Flame-retarding acc. to IEC 60332-2  
Enclosure rating per IEC 60529 or 20653, only in screwed state with the associated mating piece.

Connector Drawings



Wiring Diagrams

