

Basic features

Approval/Conformity	CE UKCA cULus WEEE
Base type deviation	Shielded pigtail contacts housing
Basic standard	IEC 60947-5-2 IEC 60947-5-7

Display/Operation

Function indicator	Adjustment indicator
Power indicator	no

Electrical connection

Bending radius min., fixed cable	5 x D
Bending radius min., flexible cable	10 x D
Cable diameter D	4.5...4.7 mm
Cable length L	1.5 m
Connection	M12x1-Male, 3-pin, A-coded
Connection type	Cable with connector, 1.50 m, PUR
Polarity reversal protected	yes
Protection against device mix-ups	yes
Short-circuit protection	yes

Electrical data

Limit frequency -3 dB	500 Hz
Load resistance RL min.	2000 Ohm
No-load current I ₀ max. at U _e	10 mA
Operating voltage U _b	15...30 VDC
Rated insulation voltage U _i	75 V DC
Rated operating voltage U _e DC	24 V
Ripple max. (% of U _e)	15 %
Slope U	2.50 V/mm

Environmental conditions

Ambient temperature	-10...70 °C
Contamination scale	3
EN 60068-2-27, Shock	Half-sinus, 30 g _n , 11 ms
EN 60068-2-6, Vibration	55 Hz, amplitude 1 mm, 3x30 min
IP rating	IP67

Functional safety

MTTF (40 °C)	640 a
--------------	-------

Interface

Analog output	Analog, voltage 0...10 V
Output characteristic	falling on approach
Output voltage at SI max.	10 V
Output voltage at SI min.	0 V
Output voltage at Se	5 V

Material

Cable shield	yes
Housing material	Brass, nickel-plated
Material jacket	PUR
Material sensing surface	PBT

Range/Distance

Linearity range SI	1...5 mm
Measuring range	1...5 mm
Non-linearity max.	$\pm 120 \mu\text{m}$
Repeat accuracy per BWN	$\pm 8 \mu\text{m}$
Temperature drift max. from end value	$\pm 5.0 \%$

Mechanical data

Dimension	$\varnothing 18 \times 36 \text{ mm}$
Installation	for flush mounting
Mounting length	30.0 mm
Size	M18x1
Tightening torque	25 Nm

Remarks


When used in Balluff clamping holders, U_a may be reduced by max. 10%

Values referenced to axial approach of St 37 target. For other materials correction factors are applied.

Scattering (e.g. due to manufacturing tolerances) is described by the tolerance T at S_e . This can be approximated using the formula: $T = (s_{l\max} + s_{l\min}) / 20 = \pm xx \text{ mm}$.

For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

Connector Drawings**Wiring Diagrams**

Technical Drawings

