



#### Basic features

|                     |                             |
|---------------------|-----------------------------|
| Additional features | Factor 1<br>Weld immune     |
| Approval/Conformity | CE<br>UKCA<br>cULus<br>WEEE |
| Basic standard      | IEC 60947-5-2               |
| Trademark           | Factor 1                    |

#### Display/Operation

|                    |     |
|--------------------|-----|
| Function indicator | yes |
| Power indicator    | no  |

#### Electrical connection

|                                   |                            |
|-----------------------------------|----------------------------|
| Connection                        | M12x1-Male, 4-pin, A-coded |
| Polarity reversal protected       | yes                        |
| Protection against device mix-ups | yes                        |
| Short-circuit protection          | yes                        |

#### Electrical data

|   |               |
|---|---------------|
| Load capacitance max. at Ue                   | 1 $\mu$ F     |
| Magnetic field strength, interference field   | 100 kA/m      |
| Min. operating current I <sub>m</sub>         | 0 mA          |
| No-load current I <sub>o</sub> max., damped   | 33 mA         |
| No-load current I <sub>o</sub> max., undamped | 25 mA         |
| Operating voltage U <sub>b</sub>              | 10...30 VDC   |
| Output resistance R <sub>a</sub>              | 33.0 kOhm + D |
| Rated insulation voltage U <sub>i</sub>       | 75 V DC       |
| Rated operating current I <sub>e</sub>        | 200 mA        |
| Rated operating voltage U <sub>e</sub> DC     | 24 V          |
| Rated short circuit current                   | 100 A         |
| Ready delay t <sub>v</sub> max.               | 30 ms         |
| Ripple max. (% of U <sub>e</sub> )            | 15 %          |
| Switching frequency                           | 80 Hz         |
| Utilization category                          | DC-13         |
| Voltage drop static max.                      | 2 V           |

#### Environmental conditions

|                         |                                       |
|-------------------------|---------------------------------------|
| Ambient temperature     | -25...70 °C                           |
| Contamination scale     | 3                                     |
| EN 60068-2-27, Shock    | Half-sinus, 30 g <sub>n</sub> , 11 ms |
| EN 60068-2-6, Vibration | 55 Hz, amplitude 1 mm, 3x30 min       |
| IP rating               | IP67                                  |
| Magnetic field immune   | magnetic field immune (AC/DC)         |

#### Functional safety

|              |       |
|--------------|-------|
| MTTF (40 °C) | 260 a |
|--------------|-------|

#### Interface

|                  |                        |
|------------------|------------------------|
| Switching output | PNP normally open (NO) |
|------------------|------------------------|

#### Material

|                          |                 |
|--------------------------|-----------------|
| Housing material         | Stainless steel |
| Material sensing surface | Stainless steel |

#### Mechanical data

|                   |                    |
|-------------------|--------------------|
| Dimension         | Ø 12 x 65 mm       |
| Installation      | for flush mounting |
| Mounting length   | 50.00 mm           |
| Size              | M12x1              |
| Tightening torque | 20 Nm              |

#### Remarks

Installation notice: flush in Al or non-ferrous metal Sr = 0.7 x Sn  
The sensor is functional again after the overload has been eliminated.  
Installation permitted only in clamp without positive stop.  
For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

#### Connector Drawings



#### Wiring Diagrams

