


Double-Ended Cordsets  
BCC M324-M314-30-304-VX8434-003  
Order Code: BCC02YU



Basic features

|                     |                     |
|---------------------|---------------------|
| Approval/Conformity | CE<br>cULus<br>WEEE |
|---------------------|---------------------|

Electrical connection

|                                     |                                        |
|-------------------------------------|----------------------------------------|
| Bending radius min., fixed cable    | 5 x D                                  |
| Bending radius min., flexible cable | 10 x D                                 |
| Cable                               | PVC gray, 0.3 m, drag chain compatible |
| Cable diameter D                    | 4.80 mm ±0.15 mm                       |
| Cable, bending cycles min.          | 2 mil.                                 |
| Conductor cross-section             | 0.34 mm <sup>2</sup>                   |
| Connection 1                        | M8x1-Female, angled, 4-pin, A-coded    |
| Connection 2                        | M8x1-Male, straight, 4-pin, A-coded    |
| Number of conductors                | 4                                      |
| System                              | Molded/Molded                          |

Electrical data

|                       |                 |
|-----------------------|-----------------|
| Operating voltage Ub  | 60 VDC / 60 VAC |
| Rated current (40 °C) | 4.0 A           |

Environmental conditions

|                                             |                         |
|---------------------------------------------|-------------------------|
| Cable temperature UL max., fixed routing    | 80 °C                   |
| Cable temperature UL max., flexible routing | 80 °C                   |
| Cable temperature, drag chain               | -5...60 °C              |
| Cable temperature, fixed routing            | -40...105 °C            |
| Cable temperature, flexible routing         | 5...105 °C              |
| IP rating                                   | IP67, IP69K/IP67, IP69K |

Interface

|                  |               |
|------------------|---------------|
| Switching output | Complementary |
|------------------|---------------|

Material

|                          |                                                                           |
|--------------------------|---------------------------------------------------------------------------|
| Cable jacket, material   | PVC                                                                       |
| Material contact carrier | PUR/PUR                                                                   |
| Material contacts        | Bronze/Brass                                                              |
| Material cover nut       | Die-cast zinc or nickel plated brass/Die-cast zinc or nickel plated brass |
| Material grip            | PUR/PUR                                                                   |


Mechanical data

|                                         |                       |
|-----------------------------------------|-----------------------|
| Acceleration max., drag chain           | 5 m/s <sup>2</sup>    |
| Cable jacket, color                     | gray                  |
| Cable length L                          | 0.30 m                |
| Cable properties                        | drag chain compatible |
| Horizontal travel permitted, drag chain | 5 m                   |
| Tightening torque pigtail               | 0.4 Nm/0.4 Nm         |
| Traverse speed max., drag chain         | 200 m/min             |
| Vertical travel permitted, drag chain   | 2 m                   |

Remarks

Cable construction acc. to UL-AWM Style 2517  
Silicone-free  
Flame-retarding acc. to IEC 60332-2  
Enclosure rating per IEC 60529 or 20653, only in screwed state with the associated mating piece.

Connector Drawings



Wiring Diagrams

