




Basic features

Approval/Conformity	CE WEEE
---------------------	------------

Electrical connection

Bending radius min., fixed cable	6 x D
Cable diameter D	6.4 mm ±0.20 mm
Conductor cross-section	26 AWG
Connection 1	M12x1-Female, straight, 12-pin, A-coded
Connection 2	M12x1-Male, straight, 8-pin, A-coded
Connection 3	M12x1-Female, straight, 5-pin, A-coded
Connector 01, version	straight
Connector 02, version	straight
Connector 03, version	straight
Number of conductors	8/10/4
Number of pins	12/8/5
System	Molded/Molded/Molded

Electrical data

Operating voltage Ub	30 VDC / 30 VAC
Rated current (40 °C)	1.5 A

Environmental conditions

Ambient temperature	-10...80 °C
Cable temperature, fixed routing	-10...80 °C


Material

Cable jacket, material	PVC
Material contact carrier	PA/PA/PA
Material contacts	Messing, gold plated/Messing, gold plated/Messing, gold plated
Material cover nut	Nickel-plated brass/Nickel-plated brass/Nickel-plated brass
Material grip	PA/PA/PA

Mechanical data

Cable jacket, color	black
Cable length L1	0.08 m
Cable length L2	0.08 m
Tightening torque pigtail	0.6 Nm/0.6 Nm/0.6 Nm

Connector Drawings



Wiring Diagrams

