




Basic features

Approval/Conformity	CE WEEE
---------------------	------------

Electrical connection

Bending radius min., fixed cable	4 x D
Bending radius min., flexible cable	7.5 x D
Cable	PUR black, 0.3 m, drag chain compatible
Cable diameter D	7.40 mm ±0.20 mm
Cable, bending cycles min.	10 mil.
Conductor cross-section	1.5 mm ²
Connection 1	7/8"-Female, straight, 4-pin
Connection 2	M12x1-Male, straight, 5-pin, L-coded
Number of conductors	4
System	Molded/Molded

Electrical data

Operating voltage U _b	60 VDC / 50 VAC
Rated current (40 °C)	9.0 A

Environmental conditions

Cable temperature, drag chain	-20...60 °C
Cable temperature, fixed routing	-40...80 °C
Cable temperature, flexible routing	-30...80 °C
IP rating	IP68/IP65, IP67, IP69K

Material

Cable jacket, material	PUR
Material contact carrier	PUR/PBT
Material contacts	Brass/Copper alloy, gold plated
Material cover nut	Die-cast zinc/Brass nickel-plated
Material grip	PUR/TPE


Mechanical data

Acceleration max., drag chain	50 m/s ²
Cable jacket, color	black
Cable length L	0.30 m
Cable properties	drag chain compatible
Horizontal travel permitted, drag chain	5 m
Tightening torque pigtail	1.5 Nm/0.6 Nm
Traverse speed max., drag chain	300 m/min

Remarks

Cable construction acc. to UL-AWM Style 20939
Flame resistance acc. to IEC 60332-1
Flame resistance per IEC 60332-1-2
Flame resistance acc. to UL 1581/1080 VW-1
Halogen-free per DIN VDE 0472 Part 815
Silicone-free
Oil resistant per DIN EN 60811-404 (VDE 0473-811-404)
Enclosure rating per IEC 60529, only in screwed state with the associated mating piece.

Connector Drawings



Wiring Diagrams

