




1) Display and control panel



Basic features

Basic standard	IEC 60947-5-2
Principle of operation	Signal amplifier
Series	SA-OH
Style	Square
	Straight connection

Electrical connection

Cable diameter D	3.70 mm
Cable length L	2 m
Conductor cross-section	0.14 mm ²
Connection	Cable, 2.00 m, PVC
Contact, surface protection	Gold plated
Number of conductors	5
Polarity reversal protected	yes
Short-circuit protection	yes

Electrical data

No-load current I ₀ max. at U _e	45 mA
Operating voltage U _b	10...30 VDC
Rated operating current I _e	200 mA
Rated operating voltage U _e DC	24 V
Switching frequency	500 Hz
Voltage drop U _d max. at I _e	2 V

Environmental conditions

Ambient temperature	-10...55 °C
IP rating	IP65

Interface

Supplementary output	Error output PNP
Switching output	PNP normally open/normally closed (NO/NC)

Material

Housing material	ABS
	PC
Material jacket	PVC

Mechanical data

Dimension	15 x 36 x 61 mm
-----------	-----------------

Optical features


Principle of optical operation	depends on sensor head
Switching function, optical	Light/dark switching

Range/Distance

Range	depends on sensor head
-------	------------------------

Connector Drawings


AC-P41




1) Sensor connection

Wiring Diagrams


51.55400001.SLD:RW



Help Views



- 1) Display
- 2) Stability
- 3) Output function
- 4) Slide switch operating modes
- 5) Jog-Switch



- 1) Display
- 2) Stability
- 3) Output function
- 4) Slide switch operating modes
- 5) Jog-Switch

Opto Symbols

