




1) Display and control panel, 2) Cover, 3) DIN rail



Basic features

Basic standard	IEC 60947-5-2
Principle of operation	Signal amplifier
Series	SA-OH
Style	Square Straight connection

Electrical connection

Connection	Connector, M8x1-Male, 4-pin
Contact, surface protection	Gold plated
Polarity reversal protected	yes
Short-circuit protection	yes

Electrical data

No-load current I_0 max. at U_e	45 mA
Operating voltage U_b	10...30 VDC
Rated operating current I_e	200 mA
Rated operating voltage U_e DC	24 V
Switching frequency	500 Hz
Voltage drop U_d max. at I_e	2 V

Environmental conditions

Ambient temperature	-10...55 °C
IP rating	IP65

Interface

Supplementary output	Error output PNP
Switching output	PNP normally open/normally closed (NO/NC)

Material

Housing material	ABS PC
------------------	-----------

Mechanical data

Dimension	15 x 36 x 61 mm
-----------	-----------------

Optical features

Principle of optical operation	depends on sensor head
Switching function, optical	Light/dark switching


Range/Distance

Range

depends on sensor head


Connector Drawings

AC-PP




1) Sensor connection


Wiring Diagrams



Help Views



- 1) Display
- 2) Stability
- 3) Output function
- 4) Slide switch operating modes
- 5) Jog-Switch



- 1) Display
- 2) Stability
- 3) Output function
- 4) Slide switch operating modes
- 5) Jog-Switch

Opto Symbols

