

#### Basic features

Approval/Conformity	CE cULus UKCA WEEE
Principle of operation	Photoelectric sensor
Style	Fork

#### Electrical connection

Connection	Connector, PVC
Polarity reversal protected	yes
Protection against device mix-ups	yes
Short-circuit protection	yes

#### Electrical data

Operating voltage $U_b$	5...24 VDC
Rated operating current $I_e$	50 mA
Rated operating voltage $U_e$ DC	24 V
Switching frequency	1 kHz

#### Environmental conditions

Ambient temperature	-25...55 °C
IP rating	IP65

#### Remarks

The sensor is functional again after the overload has been eliminated.  
Order accessories separately.

#### Interface

Switching output	PNP normally closed (NC) PNP normally open (NO)
------------------	--

#### Material

Housing material	PBT
Material jacket	PVC
Material sensing surface	PMMA

#### Mechanical data

Dimension	10 x 14,8 x 26 mm
Fork opening	5 mm
Mounting part	Through-hole 3.2 mm (2x)


#### Optical features

Light type	LED infrared
Principle of optical operation	Through-beam sensor

#### Range/Distance


Hysteresis $H$ max.	0.05 mm
Range	5 mm
Rated operating distance $S_n$	5 mm

### Connector Drawings



PIN 1: brown  
PIN 2: black  
PIN 3: white  
PIN 4: blue

### Wiring Diagrams



### Opto Symbols

