

Technical Information – BF/BFK



Pg cable glands BF, polyamide, light grey, IP 68 (5 bar, 30 min)

Model	Order no.	Note
BF 7	10000100	Pg 7; cable diameter 3-6.5 mm
BF 9	10000200	Pg 9; cable diameter 4-8 mm
BF 11	10000300	Pg 11; cable diameter 5-10 mm
BF 13	10000400	Pg 13.5; cable diameter 6-12 mm
BF 16	10000500	Pg 16; cable diameter 10-14 mm
BF 21	10000600	Pg 21; cable diameter 13-18 mm
BF 29	10000700	Pg 29; cable diameter 18-25 mm
BF 36	10000800*	Pg 36; cable diameter 22-32 mm



Pg cable glands with anti-kink protection BFK, polyamide, light grey, IP 68 (5 bar, 30 min)

Model	Order no.	Note
BFK 7	10001100	Pg 7; cable diameter 3-6.5 mm
BFK 9	10001200	Pg 9; cable diameter 4-8 mm
BFK 11	10001300	Pg 11; cable diameter 5-10 mm
BFK 13	10001400	Pg 13.5; cable diameter 6-12 mm
BFK 16	10001500	Pg 16; cable diameter 10-14 mm
BFK 21	10001600	Pg 21; cable diameter 13-18 mm

Material

- Nut / Neck - Polyamid PA6 V-2
- Oil seal - Polychloropren-Nitrilkautschuk CR/NBR

Temperature range

- -20°C / +100°C (dynamisch)
- -40°C (static, short-term)

Protection

- IP 68
- 5 bar (30 min)

Test standard

- UL 514B

Tested and certified according to:

- UL514B
- CAN/CSA C22.2 No. 18.3-04

BOPLA

A Phoenix Mecano Company

Please note!

Technical information is provided to the best of its knowledge, but does not exempt the user from checking the suitability of this information for the intended processes and purposes.