

Technical Information – MBFK

Metric cable glands with anti-kink protection MBFK, polyamide, light grey, IP 68 (5 bar, 30 min)

Model	Order no.	Note
MBFK 12-7035	12002103	M12 x 1.5; cable diameter 3-6.5 mm
MBFK 16-7035	12002210	M16 x 1.5; cable diameter 5-10 mm
MBFK 20-1-7035	12002303	M20 x 1.5; cable diameter 6-12 mm
MBFK 20-2-7035	12002306	M20 x 1.5; cable diameter 10-14 mm
MBFK 25-7035	12002401	M25 x 1.5; cable diameter 13-18 mm



Metric cable glands with anti-kink protection MBFK, polyamide, black, IP 68 (5 bar, 30 min)

Model	Order no.	Note
MBFK 12-9005	12002104	M12 x 1.5; cable diameter 3-6.5 mm
MBFK 16-9005	12002212	M16 x 1.5; cable diameter 5-10 mm
MBFK 20-1-9005	12002307	M20 x 1.5; cable diameter 6-12 mm



Material

- Nut / Neck
- Seal
- Polyamide PA6 V-2
- Polychloroprene nitrile rubber CR/NBR

Temperature range

- -20°C / +100°C (dynamic)
- -40°C (static, short-term)

Protection

- IP 68
- 5 bar (30 min)

Test standard

- UL 514B

Tested and certified according to:

- UL514B
- CAN/CSA C22.2 No. 18.3-04

BOPLA

A Phoenix Mecano Company

Please note!

Technical information is provided to the best of its knowledge, but does not exempt the user from checking the suitability of this information for the intended processes and purposes.