

## Technical Information - MEMV



### Metric EMC cable glands MEMV, brass, nickel-plated, IP 68 (5 bar, 30 min)

| Model   | Order no. | Note                               |
|---------|-----------|------------------------------------|
| MEMV 16 | 12102200* | M16 x 1.5; cable diameter 5-9 mm   |
| MEMV 20 | 12102300* | M20 x 1.5; cable diameter 9-13 mm  |
| MEMV 25 | 12102400* | M25 x 1.5; cable diameter 11-16 mm |
| MEMV 32 | 12102500* | M32 x 1.5; cable diameter 14-21 mm |
| MEMV 40 | 12102600  | M40 x 1.5; cable diameter 19-27 mm |

#### Material

- Nut / Neck
- Seal
- Slat insert
- O-ring
- Contact spring
- Brass CuZn39Pb3, galv. nickel-plated
- Polychloroprene nitrile rubber CR/NBR
- Polyamide PA6 V-2
- Nitrile Rubber NBR
- Stainless steel

#### Temperature range

- -20°C / +100°C (dynamic)
- -40°C (static, short-term)

#### Protection

- IP 68
- 5 bar (30 min)

#### Test standard

- UL 514B

Tested and certified according to:

- UL514B
- CAN/CSA C22.2 No. 18.3-04



# BOPLA

## A Phoenix Mecano Company

#### Please note!

Technical information is provided to the best of its knowledge, but does not exempt the user from checking the suitability of this information for the intended processes and purposes.