



FDD03 - 05S4 X

BLANK : w/o SAFETY APPROVALS
U : SAFETY APPROVALS

DC - DC CONVERTER 2 ~ 3W SINGLE & DUAL OUTPUT

FEATURES

- EFFICIENCY UP TO 79%
- 4:1 & 3:1 & 2:1 WIDE INPUT RANGE
- I/O ISOLATION
- SHORT CIRCUIT PROTECTION
- HIGH PERFORMANCE
- 3 YEARS WARRANTY



MODEL LIST

MODEL NO.	INPUT VOLTAGE	INPUT CURRENT (typ.)	(max.)	OUTPUT WATTAGE	OUTPUT VOLTAGE	OUTPUT CURRENT	EFF. (min.)	EFF. (typ.)	CAPACITOR LOAD (max.)
-----------	---------------	----------------------	--------	----------------	----------------	----------------	-------------	-------------	-----------------------

Single Output Models

FDD03 - 05S(U)	20~60 VDC	70 mA	180 mA	2.5 WATTS	+ 5 VDC	500 mA	72%	74%	1000 μ F
FDD03 - 12S(U)	20~60 VDC	80 mA	200 mA	3 WATTS	+ 12 VDC	250 mA	77%	79%	470 μ F
FDD03 - 15S(U)	20~60 VDC	80 mA	200 mA	3 WATTS	+ 15 VDC	200 mA	77%	79%	330 μ F
FDD03 - 05S1(U)	9~18 VDC	265 mA	340 mA	2 WATTS	+ 5 VDC	400 mA	63%	65%	1000 μ F
FDD03 - 12S1(U)	9~18 VDC	310 mA	380 mA	2.4 WATTS	+ 12 VDC	200 mA	65%	67%	470 μ F
FDD03 - 15S1(U)	9~18 VDC	285 mA	380 mA	2.4 WATTS	+ 15 VDC	160 mA	65%	67%	330 μ F
FDD03 - 05S2(U)	18~36 VDC	155 mA	200 mA	2.5 WATTS	+ 5 VDC	500 mA	67%	69%	1000 μ F
FDD03 - 12S2(U)	18~36 VDC	175 mA	230 mA	3 WATTS	+ 12 VDC	250 mA	70%	72%	470 μ F
FDD03 - 15S2(U)	18~36 VDC	175 mA	230 mA	3 WATTS	+ 15 VDC	200 mA	70%	72%	330 μ F
FDD03 - 05S3(U)	36~72 VDC	70 mA	100 mA	2.5 WATTS	+ 5 VDC	500 mA	72%	74%	1000 μ F
FDD03 - 12S3(U)	36~72 VDC	80 mA	110 mA	3 WATTS	+ 12 VDC	250 mA	77%	79%	470 μ F
FDD03 - 15S3(U)	36~72 VDC	80 mA	110 mA	3 WATTS	+ 15 VDC	200 mA	77%	79%	330 μ F
FDD03 - 05S4(U)	9~36 VDC	155 mA	440 mA	2.5 WATTS	+ 5 VDC	500 mA	67%	69%	1000 μ F
FDD03 - 12S4(U)	9~36 VDC	175 mA	510 mA	3 WATTS	+ 12 VDC	250 mA	70%	72%	470 μ F
FDD03 - 15S4(U)	9~36 VDC	175 mA	510 mA	3 WATTS	+ 15 VDC	200 mA	70%	72%	330 μ F
FDD03 - 05S5(U)	18~72 VDC	70 mA	200 mA	2.5 WATTS	+ 5 VDC	500 mA	72%	74%	1000 μ F
FDD03 - 12S5(U)	18~72 VDC	80 mA	225 mA	3 WATTS	+ 12 VDC	250 mA	77%	79%	470 μ F
FDD03 - 15S5(U)	18~72 VDC	80 mA	225 mA	3 WATTS	+ 15 VDC	200 mA	77%	79%	330 μ F

Dual Output Models

FDD03 - 05D(U)	20~60 VDC	70 mA	180 mA	2.5 WATTS	\pm 5 VDC	\pm 250 mA	73%	75%	\pm 100 μ F
FDD03 - 12D(U)	20~60 VDC	80 mA	200 mA	3 WATTS	\pm 12 VDC	\pm 125 mA	75%	77%	\pm 47 μ F
FDD03 - 15D(U)	20~60 VDC	80 mA	200 mA	3 WATTS	\pm 15 VDC	\pm 100 mA	75%	77%	\pm 22 μ F
FDD03 - 05D1(U)	9~18 VDC	265 mA	340 mA	2 WATTS	\pm 5 VDC	\pm 200 mA	63%	65%	\pm 100 μ F
FDD03 - 12D1(U)	9~18 VDC	310 mA	380 mA	2.4 WATTS	\pm 12 VDC	\pm 100 mA	65%	67%	\pm 47 μ F
FDD03 - 15D1(U)	9~18 VDC	310 mA	380 mA	2.4 WATTS	\pm 15 VDC	\pm 80 mA	65%	67%	\pm 22 μ F
FDD03 - 05D2(U)	18~36 VDC	155 mA	200 mA	2.5 WATTS	\pm 5 VDC	\pm 250 mA	66%	68%	\pm 100 μ F
FDD03 - 12D2(U)	18~36 VDC	180 mA	230 mA	3 WATTS	\pm 12 VDC	\pm 125 mA	68%	70%	\pm 47 μ F



MODEL LIST

MODEL NO.	INPUT VOLTAGE	INPUT CURRENT (typ.) (max.)	OUTPUT WATTAGE	OUTPUT VOLTAGE	OUTPUT CURRENT	EFF. (min.)	EFF. (typ.)	CAPACITOR LOAD (max.)
-----------	---------------	-----------------------------	----------------	----------------	----------------	-------------	-------------	-----------------------

Dual Output Models

FDD03 - 15D2(U)	18~36 VDC	180 mA	230 mA	3 WATTS	± 15 VDC	± 100 mA	68%	70%	± 22 µF
FDD03 - 05D3(U)	36~72 VDC	70 mA	100 mA	2.5 WATTS	± 5 VDC	± 250 mA	73%	75%	± 100 µF
FDD03 - 12D3(U)	36~72 VDC	80 mA	110 mA	3 WATTS	± 12 VDC	± 125 mA	75%	77%	± 47 µF
FDD03 - 15D3(U)	36~72 VDC	80 mA	110 mA	3 WATTS	± 15 VDC	± 100 mA	75%	77%	± 22 µF
FDD03 - 05D4(U)	9~36 VDC	155 mA	440 mA	2.5 WATTS	± 5 VDC	± 250 mA	66%	68%	± 100 µF
FDD03 - 12D4(U)	9~36 VDC	180 mA	510 mA	3 WATTS	± 12 VDC	± 125 mA	68%	70%	± 47 µF
FDD03 - 15D4(U)	9~36 VDC	180 mA	510 mA	3 WATTS	± 15 VDC	± 100 mA	68%	70%	± 22 µF
FDD03 - 05D5(U)	18~72 VDC	70 mA	200 mA	2.5 WATTS	± 5 VDC	± 250 mA	73%	75%	± 100 µF
FDD03 - 12D5(U)	18~72 VDC	80 mA	225 mA	3 WATTS	± 12 VDC	± 125 mA	75%	77%	± 47 µF
FDD03 - 15D5(U)	18~72 VDC	80 mA	225 mA	3 WATTS	± 15 VDC	± 100 mA	75%	77%	± 22 µF

SPECIFICATION

All Specifications Typical At Nominal Line, Full Load, 25°C Unless Otherwise Noticed

GENERAL

Characteristics	Conditions	min.	typ.	max.	unit
Switching frequency	Vi nom, Io nom	50			KHz
Isolation voltage	Input - Output	1,500			VDC
Isolation resistance	Input - Output, @ 500VDC	100			MΩ
Ambient temperature	Operating at Vi nom, Io nom	-40		+ 71	°C
Case temperature	Operating at Vi nom, Io nom			+ 90	°C
Derating	Vi nom		See derating curve		
Storage temperature	Non operational	-40		+ 100	°C
Relative humidity	Vi nom, Io nom	20		95	% RH
Temperature coefficient	Vi nom, Io min			± 0.02	% / °C
Dimension		L31.8 x W20.3 x H12.7			mm
MTBF	Bellcore issue 6@40°C, GB		1,640,000		Hours
Cooling	Free air convection				

INPUT SPECIFICATIONS

Characteristics	Conditions	min.	typ.	max.	unit
Input voltage range	Ta min ... Ta max, Io nom	2 : 1 18 36	9 12 24 48	18 24 36	VDC
		3 : 1 4 : 1	20 9	48 24	VDC
			18	72	VDC
No load input current	Vi nom, Io=0	12V 24V 48V		18 15 8	mA
Input voltage w/o damage	Io nom	12V 24V 48V		20 40 75	VDC
Startup voltage	Io nom	12V 24V 48V	7.2 7.2 16.1		VDC

OUTPUT SPECIFICATIONS

Characteristics	Conditions	min.	typ.	max.	unit
Output voltage accuracy	Vi nom, Io nom			± 2	%
Minimum load	Vi nom single output models dual output models (each output)	0 20			%



SPECIFICATION

All Specifications Typical At Nominal Line, Full Load, 25°C Unless Otherwise Noticed

OUTPUT SPECIFICATIONS

Characteristics	Conditions	min.	typ.	max.	unit
Line regulation	Io nom, Vi min ...Vi max			± 1	%
Load regulation	Vi nom, Io 0 ...Io nom, single output models			± 2	%
	Vi nom, Io min ...Io nom, dual output models			± 5	%
Cross regulation (Dual model)	Aymmetrical load 20% - 100% FL			± 10	%
Startup time	Vi nom, Io nom			30	ms
Transient recovery time	Vi nom, I ~ 0.5 Io nom			3	ms
Ripple & noise	Vi nom, Io nom, BW = 20MHz			300	mV
Efficiency	Vi nom, Io nom, Po / Pi	Up to 79%, See model list and efficiency curve			

CONTROL AND PROTECTION

Input reversed	External shunt diode, external fuse recommended (12Vin : 0.75A, 24Vin : 0.75A, 48Vin : 0.5A)
Output short circuit	Current limited (Auto-recovery)

APPROVALS AND STANDARD

cTUVus	UL 62368-1
TUV	EN 62368-1
CE (I)	EN 61204-3, EN 55032 Class B, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-6, EN 61000-4-8
Vibration	meet IEC 60068-2-6 (10-500 Hz, 2G, along X, Y, Z each Axis, 60 min for each Axis)



NOTE 1 : Pls refer to recommended circuit .

PHYSICAL CHARACTERISTICS

Case size	31.8 x 20.3 x 12.7 mm (1.25 x 0.8 x 0.5 inches)
Case material	Plastic
Weight	15 g
Potting material	Epoxy

MECHANISM & PIN CONFIGURATION


mm [inch]

**PIN ASSIGNMENT****GENERAL**


PIN NO.	2&3	9	10&15	11	14	16	22&23
SINGLE	Vi -	N. C.	N. C.	N. C.	Vo+	Vo -	Vi +
DUAL	Vi -	com	N. C.	Vo-	Vo+	com	Vi +

APPLICATION CIRCUIT

a. SINGLE OUTPUT MODELS :



b. DUAL OUTPUT MODELS :

**NOTE:**

a.C1=4.7µF / 100V, C2=10µF


b.C1 MUST BE ADDED WHEN APPLICATION .

c.C2 OPTIONAL TO MINIMIZE THE R & N <100mV .

d.MAX. 80% LOAD WHEN INPUT VOLTAGE AT 9-11VDC FOR 9-36VDC INPUT MODELS & 18-21VDC FOR 18-72VDC INPUT MODELS .




CIRCUIT SCHEMATIC




RECOMMENDED CIRCUIT

- Recommended filter for EN 55032 Class B compliance

SINGLE OUTPUT MODELS



DUAL OUTPUT MODELS




Note: DI - Reverse Diode (1A/100V)




- The components used in the above figure, together with the manufacturer part numbers for these components, are as follows.

	C1	C2	C3	C4	L1
FDD03-XXSX(U)	6.8 μF / 100V MLCC	4.7 μF / 100V MLCC	InF/2KV MLCC		3mH Common Choke
FDD03-XXDX(U)	6.8 μF / 100V MLCC	4.7 μF / 100V MLCC		InF/2KV MLCC	3mH Common Choke

- Recommended EN 55032 Class B filter circuit layout.



DERATING AND EFFICIENCY CURVE





FDD03 - 05S4A x

BLANK : w/o SAFETY APPROVALS
U : SAFETY APPROVALS

DC - DC CONVERTER 2.5 ~ 3W SINGLE & DUAL OUTPUT

FEATURES

- 4:1 WIDE INPUT RANGE
- DIP24 PACKAGE
- I/O, O/O ISOLATION
- SHORT CIRCUIT PROTECTION
- HIGH PERFORMANCE
- 3 YEARS WARRANTY



MODEL LIST

MODEL NO.	INPUT VOLTAGE	INPUT CURRENT (typ.)	(max.)	OUTPUT WATTAGE	OUTPUT VOLTAGE	OUTPUT CURRENT	EFF. (min.)	EFF. (typ.)	CAPACITOR LOAD (max.)
-----------	---------------	----------------------	--------	----------------	----------------	----------------	-------------	-------------	-----------------------

Single Output Models

FDD03 - 05S4A(U)	9~36 VDC	160 mA	440 mA	2.5 WATTS	+ 5 VDC	500 mA	65%	67%	1000 μF
FDD03 - 12S4A(U)	9~36 VDC	180 mA	530 mA	3 WATTS	+ 12 VDC	250 mA	68%	70%	470 μF
FDD03 - 15S4A(U)	9~36 VDC	180 mA	530 mA	3 WATTS	+ 15 VDC	200 mA	68%	70%	330 μF
FDD03 - 05S5A(U)	18~72 VDC	75 mA	205 mA	2.5 WATTS	+ 5 VDC	500 mA	70%	72%	1000 μF
FDD03 - 12S5A(U)	18~72 VDC	80 mA	235 mA	3 WATTS	+ 12 VDC	250 mA	75%	77%	470 μF
FDD03 - 15S5A(U)	18~72 VDC	80 mA	235 mA	3 WATTS	+ 15 VDC	200 mA	75%	77%	330 μF

Dual Output Models

FDD03 - 05D4A(U)	9~36 VDC	155 mA	440 mA	2.5 WATTS	± 5 VDC	± 250 mA	66%	68%	± 100 μF
FDD03 - 12D4A(U)	9~36 VDC	180 mA	530 mA	3 WATTS	± 12 VDC	± 125 mA	68%	70%	± 47 μF
FDD03 - 15D4A(U)	9~36 VDC	180 mA	530 mA	3 WATTS	± 15 VDC	± 100 mA	68%	70%	± 22 μF
FDD03 - 05D5A(U)	18~72 VDC	70 mA	205 mA	2.5 WATTS	± 5 VDC	± 250 mA	72%	74%	± 100 μF
FDD03 - 12D5A(U)	18~72 VDC	80 mA	235 mA	3 WATTS	± 12 VDC	± 125 mA	75%	77%	± 47 μF
FDD03 - 15D5A(U)	18~72 VDC	80 mA	235 mA	3 WATTS	± 15 VDC	± 100 mA	75%	77%	± 22 μF

Double Output Models

FDD03 - 0505D4A(U)	9~36 VDC	160 mA	440 mA	2.5 WATTS	5 / 5 VDC	250 / 250 mA	66%	68%	100 μF
FDD03 - 1212D4A(U)	9~36 VDC	180 mA	530 mA	3 WATTS	12 / 12 VDC	125 / 125 mA	68%	70%	47 μF
FDD03 - 1515D4A(U)	9~36 VDC	180 mA	530 mA	3 WATTS	15 / 15 VDC	100 / 100 mA	68%	70%	22 μF
FDD03 - 0505D5A(U)	18~72 VDC	70 mA	205 mA	2.5 WATTS	5 / 5 VDC	250 / 250 mA	72%	74%	100 μF
FDD03 - 1212D5A(U)	18~72 VDC	80 mA	235 mA	3 WATTS	12 / 12 VDC	125 / 125 mA	75%	77%	47 μF
FDD03 - 1515D5A(U)	18~72 VDC	80 mA	235 mA	3 WATTS	15 / 15 VDC	100 / 100 mA	75%	77%	22 μF

NOTE :

MAX. 80% LOAD WHEN INPUT VOLTAGE AT 9-11VDC FOR 9-36VDC INPUT MODELS &
18-21VDC FOR 18-72VDC INPUT MODELS.

SPECIFICATION

All Specifications Typical At Nominal Line, Full Load, 25°C Unless Otherwise Noticed

GENERAL

Characteristics	Conditions	min.	typ.	max.	unit
Switching frequency	Vi nom, Io nom	50			KHz
Isolation voltage	Input - Output	1,500			VDC
Isolation resistance	Input - Output, @ 500VDC	100			MΩ
Ambient temperature	Operating at Vi nom, Io nom	-40		+71	°C
Case temperature	Operating at Vi nom, Io nom			+90	°C
Derating	Vi nom	See derating curve			
Storage temperature	Non operational	-40		+100	°C
Relative humidity	Vi nom, Io nom	20		95	% RH
Temperature coefficient	Vi nom, Io min			± 0.02	% / °C
Dimension		L31.8 x W20.3 x H12.7			
MTBF	Bellcore issue 6@40°C, GB		1,640,000		Hours
Cooling	Free air convection				

INPUT SPECIFICATIONS

Characteristics	Conditions	min.	typ.	max.	unit
Input voltage range	Ta min ... Ta max, Io nom	9	24	36	VDC
		18	48	72	VDC
No load input current	Vi nom, Io=0	24V 48V		15 8	mA
Input voltage w/o damage	Io nom	24V 48V		40 75	VDC
Startup voltage	Io nom	24V 48V	7.2 16.1		VDC

OUTPUT SPECIFICATIONS

Characteristics	Conditions	min.	typ.	max.	unit
Output voltage accuracy	Vi nom, Io nom			± 2	%
Minimum load	Vi nom single output models	0			%
	dual output models (each output)	20			%
Line regulation	Io nom, Vi min ... Vi max			± 1	%
Load regulation	Vi nom, Io 0 ... Io nom, single output models			± 2	%
	Vi nom, Io min ... Io nom, dual output models			± 5	%
Cross regulation (Dual model)	Asymmetrical load 20% - 100% FL			± 10	%
Startup time	Vi nom, Io nom			30	ms
Transient recovery time	Vi nom, I ~ 0.5 Io nom			3	ms
Ripple & noise	Vi nom, Io nom, BW = 20MHz			150	mV
Efficiency	Vi nom, Io nom, Po / Pi	Up to 77%, See model list and efficiency curve			

CONTROL AND PROTECTION

Remote ON / OFF	ON: opened or 5~10 VDC applied, reference to input GND OFF: -0.3~2 VDC applied, reference to input GND
Input reversed	External shunt diode, external fuse recommended (24Vin : 0.75A, 48Vin : 0.5A)
Output short circuit	Current limited (Auto-recovery)

APPROVALS AND STANDARD

cTUVus	UL 62368-1
TUV	EN 62368-1
CE (I)	EN 61204-3, EN 55032 Class B, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-6, EN 61000-4-8
Vibration	meet IEC 60068-2-6 (10-500 Hz, 2G, along X, Y, Z each Axis, 60 min for each Axis)

NOTE 1 : Pls refer to recommended circuit .





PHYSICAL CHARACTERISTICS

Case size	31.8 x 20.3 x 12.7 mm (1.25 x 0.8 x 0.5 inches)
Case material	Plastic
Weight	15 g
Potting material	Epoxy

MECHANISM & PIN CONFIGURATION

mm [inch]



BOTTOM VIEW

GENERAL TOLERANCE


0.00[0.00] - 30.00[1.18]	$\pm 0.30[0.01]$
30.00[1.18] - 120.00[4.72]	$\pm 0.50[0.02]$

PIN ASSIGNMENT**GENERAL**


PIN NO.	I&2	9	I0&I1	I2	I3	I5	I6	20	23&24
SINGLE	Vi+	NO PIN	NO PIN	Vo -	Vo +	NO PIN	NO PIN	ON/OFF	Vi -
DUAL	Vi+	NO PIN	com	NO PIN	Vo -	Vo +	NO PIN	ON/OFF	Vi -
DOUBLE	Vi+	Vo1-	NO PIN	Vo1+	Vo2+	NO PIN	Vo2-	ON/OFF	Vi -

CIRCUIT SCHEMATIC


• Block diagram for FDD03A(U) series with single output



• Block diagram for FDD03A(U) series with dual output




• Block diagram for FDD03A(U) series with double output



RECOMMENDED CIRCUIT

- Recommended filter for EN 55032 Class B compliance




Note: DI - Reverse Diode (1A / 100V)

- The components used in the above figure, together with the manufacturer part numbers for these components, are as follows.

	C1	C2	C3	C4	C5	C6	L1
FDD03-XXSXA(U)	6.8μF / 100V MLCC	4.7μF / 100V MLCC	InF/2KV MLCC				3mH Common Choke
FDD03-XXDXA(U)	6.8μF / 100V MLCC	4.7μF / 100V MLCC		InF/2KV MLCC			3mH Common Choke
FDD03-XXXXDXA(U)	6.8μF / 100V MLCC	4.7μF / 100V MLCC			InF/2KV MLCC	InF/2KV MLCC	3mH Common Choke

- Recommended EN 55032 Class B filter circuit layout.



DERATING AND EFFICIENCY CURVE

